



Alto L

The compact alternative - with respect to size, weight and price/performance ratio.

Product description

- Rung depth 30 mm.
- Very lightweight but extremely stable.
- Outside width: 350 mm.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping.
- High strength, non-twist rung/stile connections.
- Rungs and stiles made from aluminium extrusions.

Product features

Coating: natural
 Connection between stiles and rungs/stiles: flanged
 Load: max. 150 kg
 Material: aluminium
 Product type: Flanged single ladder with rungs
 Tread depth: 30 mm
 Type of rungs/treads: serrated
 Vertical distance between each rung/tread: 270 mm



Hints and special features

Complies with EN 131 Professional.

Product variants

Order number	Number of rungs	Overall length	Stile depth	Transport dimensions	Weight	Wide crosspiece	Working height
41547	7	2.21 m	58 mm	2.210 mm × 350 mm × 60 mm	4 kg		3.05 m
41548	8	2.49 m	58 mm	2.490 mm × 350 mm × 60 mm	4.4 kg		3.35 m
41550	10	3.05 m	58 mm	3.050 mm × 350 mm × 60 mm	6.1 kg	0.79 m	3.9 m
41552	12	3.61 m	58 mm	3.610 mm × 350 mm × 60 mm	7 kg	0.79 m	4.4 m
41554	14	4.17 m	62 mm	4.170 mm × 350 mm × 65 mm	8 kg	0.79 m	4.95 m
41556	16	4.73 m	68 mm	4.730 mm × 350 mm × 70 mm	9.2 kg	0.89 m	5.5 m
41558	18	5.29 m	73 mm	5.290 mm × 350 mm × 80 mm	10.5 kg	0.89 m	6.05 m
41560	20	5.85 m	73 mm	5.850 mm × 350 mm × 80 mm	11.5 kg	0.99 m	6.6 m



Order number	Number of rungs	Overall length	Stile depth	Transport dimensions	Weight	Wide crosspiece	Working height
41562	22	6.41 m	73 mm	6.410 mm × 350 mm × 80 mm	13.2312 kg	0.99 m	7.15 m
41564	24	6.98 m	85 mm	6.970 mm × 350 mm × 90 mm	14.4 kg	1.1 m	7.7 m