

Strato DL

The inexpensive alternative for safe ascent and quick and flexible application.

Product description

- The inexpensive alternative for safe ascent and quick and flexible application.
- Sturdy triangular rungs made from extruded profiles that have a horizontal stepping surface when in the use position.
- Outside width: 350 mm.
- The unique rung design creates a wide stepping surface.
- Stiles made from extruded aluminium sections for maximum stability.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping.
- High strength, non-twist rung/stile connections.



to the product



Product features

Coating: natural
 Connection between stiles and rungs/stiles: flanged
 Load capacity: max. 150 kg
 Material: aluminium
 Standards: EN 131 professional
 Tread depth: 38 mm
 Type of rungs/treads: serrated
 Vertical distance between each rung/tread: 265 mm
 Warranty: 10 years

Hints and special features

Complies with EN 131 Professional.

Product variants

Order number	Number of rungs	Overall length	Stile depth	Transport dimensions	Weight	Wide crosspiece	Working height
44808	8	2.42 m	58 mm	2.420 mm × 360 mm × 60 mm	4.3 kg		3.3 m
44810	10	2.98 m	58 mm	2.980 mm × 360 mm × 60 mm	5.3 kg		3.85 m
44812	12	3.54 m	68 mm	3.540 mm × 360 mm × 70 mm	7.9 kg	0.79 m	4.4 m
44814	14	4.11 m	73 mm	4.110 mm × 360 mm × 75 mm	9.2 kg	0.79 m	4.9 m
44816	16	4.67 m	73 mm	4.660 mm × 360 mm × 75 mm	10.1 kg	0.89 m	5.45 m
44818	18	5.23 m	73 mm	5.220 mm × 360 mm × 75 mm	11.2 kg	0.89 m	6 m
44819	20	5.9 m	73 mm	5.780 mm × 360 mm × 75 mm	12.4 kg	0.99 m	6.55 m
