

# **Comfortstep LH**

These flexible ladders ensure safe access to shelving and can be adapted to the required height.

#### **Product description**

- These flexible ladders ensure safe access to shelving and can be adapted to the required height.
- The hook-on shelf ladders have two hooks for the guiderail and additional hooks for vertical storage on the shelf.

### **Product features**

Coating: anodised

Connection between stiles and rungs/stiles: bolted

Load capacity: max. 150 kg Material: aluminium

Standards: EN 131 professional

Tread depth: 80 mm

Type of rungs/treads: padding on front tread edges Vertical distance between each rung/tread: 250 mm

Warranty: 10 years





## Hints and special features

Please quote the distance between the floor and the top edge of the tubular rail when ordering! Complies with EN 131 Professional.

#### **Product variants**

Order number	Number of treads	Transport dimensions	Vertical hook-on height	Weight	Working height	maximum vertical hook-on height	minimum vertical hook-on height
41402	6	1.660 mm × 380 mm × 100 mm	=1,45m-=1,69 m	4.5 kg	2.75 m	1.69 m	1.45 m
41403	7	1.900 mm × 380 mm × 100 mm	=1,7m-=1,94 m	5.2 kg	3 m	1.94 m	1.7 m
41404	8	2.140 mm × 380 mm × 100 mm	=1,95m-=2,19 m	5.9 kg	3.25 m	2.19 m	1.95 m
41405	9	2.380 mm × 380 mm × 140 mm	=2,2m-=2,44 m	6.6 kg	3.5 m	2.44 m	2.2 m
41406	10	2.300 mm × 380 mm × 150 mm	=2,45m-=2,69 m	7.3 kg	3.75 m	2.69 m	2.45 m