

## Saferstep LH

These flexible ladders ensure safe access to shelving and can be adapted to the required height.

## **Product description**

- These flexible ladders ensure safe access to shelving and can be adapted to the required height.
- The hook-on shelf ladders have two hooks for the guiderail and additional hooks for vertical storage on the shelf.



Coating: anodised

Connection between stiles and rungs/stiles: flanged

Load capacity: max. 150 kg Material: aluminium

Standards: EN 131 professional

Tread depth: 80 mm

Type of rungs/treads: Safer Step

Vertical distance between each rung/tread: 265 mm

Warranty: 10 years







## Hints and special features

Please quote the distance between the floor and the top edge of the tubular rail when ordering! Complies with EN 131 Professional.

## **Product variants**

Order number	Number of treads	Transport dimensions	Vertical hook-on height	Weight	maximum vertical hook-on height	minimum vertical hook-on height
1041356	6	1.940 mm × 423 mm × 73 mm	=1,31m-=1,78 m	7 kg	1.78 m	1.31 m
1041358	8	2.500 mm × 423 mm × 73 mm	=1,79m-=2,28 m	10.2 kg	2.28 m	1.79 m
1041360	10	3.060 mm × 423 mm × 73 mm	=2,29m-=2,82 m	11.3 kg	2.82 m	2.29 m
1041362	12	3.620 mm × 423 mm × 73 mm	=2,83m-=3,35 m	12.5 kg	3.35 m	2.83 m
1041364	14	4.180 mm × 423 mm × 73 mm	=3,36m-=3,87 m	13.8 kg	3.87 m	3.36 m