

# Everest 2DE

Safe, flexible and suitable for great heights, with an excellent price/performance ratio.

## Product description

- Safe, flexible and suitable for great heights, with an excellent price/performance ratio.
- Convenient and precise rung-by-rung height adjustment in increments of 280 mm.
- Both parts of the ladder can also be used separately as single ladders for Order Nos. 44834 and 44820
- Sturdy triangular rungs made from extruded profiles that have a horizontal stepping surface when in the use position.
- Outside width of lower ladder: 420 mm.
- Positive guide fittings of aluminium extruded section.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping.



to the product



## Product features

Coating: natural  
 Connection between stiles and rungs/stiles: flanged  
 External width of lower ladder: 420 mm  
 Load capacity: max. 150 kg  
 Material: aluminium  
 Standards: EN 131 professional  
 Tread depth: 38 mm  
 Type of rungs/treads: serrated  
 Vertical distance between each rung/tread: 265 mm  
 Warranty: 10 years

## Hints and special features

Complies with EN 131 Professional.

## Product variants

Order number	Number of rungs	Number of rungs	Overall length, extended	Overall length, retracted	Stile depth	Transport dimensions	Weight
44834	8	2 × 8	3.8 m	2.42 m	58 mm	2.420 mm × 420 mm × 115 mm	9.3 kg
44820	10	2 × 10	4.93 m	2.98 m	68 mm	2.980 mm × 430 mm × 120 mm	11.3 kg
44822	12	2 × 12	6.05 m	3.54 m	68 mm	3.540 mm × 430 mm × 135 mm	15.4 kg
44824	14	2 × 14	7.17 m	4.1 m	85 mm	4.100 mm × 430 mm × 135 mm	17.8 kg
44826	16	2 × 16	8.29 m	4.66 m	85 mm	4.660 mm × 430 mm × 145 mm	21.5 kg
44828	18	2 × 18	9.17 m	5.23 m	85 mm	5.230 mm × 430 mm × 145 mm	23.9 kg

Order number	Wide crosspiece	Working height
44834	0.8 m	4.6 m
44820	0.9 m	5.65 m
44822	1 m	6.8 m



Order number	Wide crosspiece	Working height
44824	1.1 m	7.85 m
44826	1.2 m	8.7 m
44828	1.2 m	9.8 m