

Everest EFA 2E

Plastic ladder for access to great heights, for use in electrical and chemical environments.

Product description

- Plastic ladder for access to great heights, for use in electrical and chemical environments.
- Stiles and rungs made of glass-fibre-reinforced plastic for particularly high chemical resistance.
- Complies with the high-voltage test for ladders of insulating material in accordance with DIN EN 61478 and VDE 0682 Section 6.5 Category 1/30 KV.
- Convenient and precise rung-by-rung height adjustment in increments of 280 mm.
- Both parts of the ladder can also be used separately as single ladders for Order Nos. 41288-41290.
- Stiles and rungs (30 mm x 30 mm) made from glass-fibre-reinforced plastic for particularly high chemical resistance.
- Suitable for use in high-voltage environments (1,000 V AC, 1,500 V DC).
- Outside width of lower ladder: 430 mm.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping.



to the product



Hints and special features

Complies with EN 131 Professional.

Product features

External width of lower ladder: 420 mm
 Load capacity: max. 150 kg
 Material: Glass-fibre reinforced plastic
 Standards: EN 131 professional
 Stile depth: 73 mm
 Tread depth: 30 mm
 Type of rungs/treads: serrated
 Vertical distance between each rung/tread: 270 mm
 Warranty: 10 years

Product variants

Order number	Number of rungs	Number of rungs	Overall length, extended	Overall length, retracted	Transport dimensions	Weight	Wide crosspiece
41288	8	2 x 8	4.17 m	2.44 m	2.500 mm x 430 mm x 125 mm	14.3 kg	0.8 m
41290	10	2 x 10	4.91 m	2.95 m	2.950 mm x 430 mm x 150 mm	19.5 kg	0.9 m
41292	12	2 x 12	6.03 m	3.51 m	3.510 mm x 430 mm x 150 mm	23.3 kg	1 m

Order number	Working height
41288	4.95 m



Order number	Working height
-----------------	----------------

41290	5.7 m
-------	-------

41292	6.75 m
-------	--------