

Scana S

High degree of comfort while working due to abrasion-resistant, anodised stiles and large storage tray.

Product description

- High degree of comfort while working due to abrasion-resistant, anodised stiles and large storage tray.
- Large standing platform with anti-slip serrated surface.
- Tread depth 80 mm.
- Wear-resistant, anodised stiles.
- Practical storage tray with plenty of space for tools and small parts.
- High-strength Perlon straps prevent splay, from 6 rungs.
- Optimal platform stability thanks to extruded aluminium sections.
- Two plastic locating guides lock steps together when it's closed.



Coating: anodised

Connection between stiles and rungs/stiles: riveted

Load capacity: max. 150 kg Material: aluminium Platform length: 250 mm Platform width: 250 mm Standards: EN 131 professional

Stile depth: 40 mm Stile depth: 40 mm

Stile depth steps/back stay: 40mm / 40mm

Storage tray: Plastic Tread depth: 80 mm

Type of rungs/treads: serrated

Vertical distance between each rung/tread: 216 mm

Warranty: 10 years

Product variants

Order number	Anti-splay mechanism	Base	Number of rungs, incl. platform	Overall base width	Overall length	Platform height	Transport dimensions
44153		0,67 m × 0,41 m	3	0.41 m	1.36 m	0.59 m	1.370 mm × 410 mm × 110 mm
44154		0,82 m × 0,43 m	4	0.43 m	1.59 m	0.81 m	1.600 mm × 440 mm × 110 mm
44155		0,96 m × 0,46 m	5	0.46 m	1.82 m	1.03 m	1.830 mm × 460 mm × 110 mm
44156	Belt strap	1,1 m × 0,48 m	6	0.48 m	2.05 m	1.24 m	2.060 mm × 490 mm × 110 mm





Hints and special features

Complies with EN 131 Professional.



Order number	Anti-splay mechanism	Base	Number of rungs, incl. platform	Overall base width	Overall length	Platform height	Transport dimensions
44157	Belt strap	1,25 m × 0,51 m	7	0.51 m	2.29 m	1.47 m	2.290 mm × 510 mm × 110 mm
44158	Belt strap	1,7 m × 0,53 m	8	0.53 m	2.52 m	1.7 m	2.520 mm × 530 mm × 110 mm

Order number	Vertical ladder height	Weight	Working height
44153	1.2 m	3.7 kg	2.6 m
44154	1.42 m	4.4 kg	2.8 m
44155	1.64 m	5.1 kg	3 m
44156	1.85 m	5.9 kg	3.25 m
44157	2.08 m	6.6 kg	3.5 m
44158	2.31 m	8 kg	3.7 m