

# Seventec B

Stable and comfortable: deep treads for stability, smooth rails for a comfortable grip.


## Product description

- Stable and comfortable: deep treads for stability, smooth rails for a comfortable grip.
- Treads 85 mm deep for safe standing.
- Sturdy hinged connection integrated in the treads.
- High stability thanks to fold-down locking bar on both sides.
- Reinforced with a patented 7-point connection system and a central steel rod that runs right through the tread.
- Treads and stiles made from extruded aluminium sections.
- Non-slip plastic end caps.



## Product features

Anti-splay mechanism: Rigid locking bar  
 Coating: natural  
 Connection between stiles and rungs/stiles: riveted  
 Load capacity: max. 150 kg  
 Material: aluminium  
 Standards: EN 131 professional  
 Stile depth: 87 mm  
 Tread depth: 85 mm  
 Type of rungs/treads: serrated  
 Vertical distance between each rung/tread: 218 mm  
 Warranty: 10 years



## Hints and special features

Complies with EN 131 Professional.

## Product variants

| Order number | Base            | Number of treads | Number of treads | Overall base width | Overall length | Transport dimensions               | Vertical ladder height |
|--------------|-----------------|------------------|------------------|--------------------|----------------|------------------------------------|------------------------|
| 40353        | 0,71 m × 0,41 m | 3                | 2 × 3            | 0.41 m             | 0.74 m         | 740 mm × 410 mm × 230 mm           | 0.66 m                 |
| 40354        | 0,86 m × 0,43 m | 4                | 2 × 4            | 0.43 m             | 0.97 m         | 970 mm × 430 mm × approx. 230 mm   | 0.88 m                 |
| 40355        | 1,02 m × 0,45 m | 5                | 2 × 5            | 0.45 m             | 1.2 m          | 1.200 mm × 460 mm × approx. 230 mm | 1.1 m                  |
| 40356        | 1,18 m × 0,47 m | 6                | 2 × 6            | 0.47 m             | 1.43 m         | 1.430 mm × 480 mm × 230 mm         | 1.31 m                 |
| 40357        | 1,34 m × 0,5 m  | 7                | 2 × 7            | 0.5 m              | 1.66 m         | 1.660 mm × 500 mm × 230 mm         | 1.53 m                 |
| 40358        | 1,5 m × 0,52 m  | 8                | 2 × 8            | 0.52 m             | 1.9 m          | 1.890 mm × 530 mm × 230 mm         | 1.74 m                 |
| 40360        | 1,81 m × 0,56 m | 10               | 2 × 10           | 0.56 m             | 2.35 m         | 2.350 mm × 580 mm × 230 mm         | 2.18 m                 |

| Order number | Weight | Working height |
|--------------|--------|----------------|
|--------------|--------|----------------|



| Order number | Weight  | Working height |
|--------------|---------|----------------|
| 40353        | 4.5 kg  | 2.25 m         |
| 40354        | 6 kg    | 2.45 m         |
| 40355        | 7.5 kg  | 2.65 m         |
| 40356        | 9 kg    | 2.85 m         |
| 40357        | 10.5 kg | 3.1 m          |
| 40358        | 12 kg   | 3.35 m         |
| 40360        | 15.5 kg | 3.75 m         |