



Variotec V

Multifunctional, extendible ladder suitable for use on stairs, with compact transport dimensions and in sturdy, durable design.

Product description

- The ladder can be adjusted to the desired working height in increments of 280 mm.
- Folds down to a space-saving compact size for transport.
- With self-locking steel hinges; order no. 42396 with reinforced aluminium hinge.
- Stiles made from extruded aluminium sections for maximum stability.
- High strength, non-twist rung/stile connections.



Product features

Coating: natural

Connection between stiles and rungs/stiles: flanged

Load: max. 150 kg

Material: aluminium

Product type: Flanged telescopic multipurpose ladder, 4 sections

Stile depth: 60 mm

Stile depth: 70 mm

Stile depth: 60mm / 70mm

Tread depth: 30 mm

Type of rungs/treads: serrated

Vertical distance between each rung/tread: 265 mm

Hints and special features

Ideal for use on steps/stairs as a result of rung-by-rung height adjustment on both sides.

Does not comply with EN131-1+2.

Product variants

Order number	Dimensions, folded	Length	Length as lean-to ladder	Length as trestle	Number of rungs	Number of rungs	Transport dimensions	Weight	Width	Working height as lean-to ladder	Working height as stepladder
42394	1,3 m × 0,56 m × 0,21 m	1.3 m	4.17 m	2.2 m	4	4 × 4	1.310 mm × 560 mm × 200 mm	13 kg	0.56 m	4.95 m	3.4 m
42395	1,58 m × 0,63 m × 0,21 m	1.58 m	5.29 m	2.7 m	5	4 × 5	1.580 mm × 630 mm × 200 mm	16 kg	0.63 m	6.05 m	3.9 m
42396	1,86 m × 0,7 m × 0,21 m	1.86 m	6.4 m	3.09 m	6	4 × 6	1.860 mm × 700 mm × 210 mm	20 kg	0.7 m	7.1 m	4.4 m