

Combimaster Plus X

Two ladders in one: combined stepladder and extension ladder for safe standing.

Product description

- Two ladders in one: combined stepladder and extension ladder for safe standing.
- Can be used as a two-section push-up ladder or as a ladder with double-sided access.
- High-strength Perlon straps with sewn-in fixing tab to prevent splaying.
- Stiles made from extruded aluminium sections for maximum stability.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping.
- High strength, non-twist rung/stile connections.



Product features

Coating: natural
 Connection between stiles and rungs/stiles: flanged
 Load capacity: max. 150 kg
 Material: aluminium
 Standards: EN 131 professional
 Tread depth: 30 mm
 Type of rungs/treads: serrated
 Vertical distance between each rung/tread: 265 mm
 Warranty: 10 years



Hints and special features

Complies with EN 131 Professional.

Product variants

Order number	Length as trestle	Number of rungs	Number of rungs	Overall length, extended	Overall length, retracted	Stile depth	Transport dimensions
42566	1.75 m	6	2 × 6	2.98 m	1.86 m	58 mm	1.860 mm × 420 mm × 125 mm
42568	2.27 m	8	2 × 8	4.1 m	2.42 m	58 mm	2.420 mm × 420 mm × 125 mm
42570	2.8 m	10	2 × 10	4.94 m	2.98 m	58 mm	2.980 mm × 420 mm × 125 mm
42572	3.33 m	12	2 × 12	6.06 m	3.54 m	73 mm	3.540 mm × 420 mm × 135 mm
42574	3.86 m	14	2 × 14	7.19 m	4.1 m	85 mm	4.110 mm × 420 mm × 140 mm
42576	4.39 m	16	2 × 16	8.31 m	4.67 m	98 mm	4.670 mm × 420 mm × 150 mm

Order number	Weight	Wide crosspiece	Working height
42566	7.9 kg	0.8 m	3.8 m
42568	10.1 kg	0.8 m	4.9 m
42570	12.2 kg	0.9 m	5.7 m



Order number	Weight	Wide crosspiece	Working height
42572	15.3 kg	1 m	6.8 m
42574	18.1 kg	1.1 m	7.9 m
42576	22 kg	1.2 m	9 m