

Roof safety hooks compliant with DIN EN 517

Product description

- At least two roof safety hooks in staggered arrangement are required to ensure secure fastening. For ladders with a length of up to 4.20 m, two load-bearing roof safety hooks are required.
- "One extra hook is required for each ladder section with a length of 2.00 m or 2.80 m

Product features

Warranty: Missing translation



to the product



Hints and special features

Supporting safety roof hooks must be fitted centrally on the rafters. Smallest rafter circumference: 60 x 80 mm.

Product variants

| Order number | Colour | Material | Transport dimensions | Version | Weight |
|--------------|-------------------|----------------------|-------------------------|--|--------|
| 40969 | Steel, galvanised | Steel, galvanised | 450 mm × 210 mm × 30 mm | for pantiles and double depression interlocking ti | 1.2 kg |
| 40490 | Copper-brown | Powder-coated steel. | 430 mm × 200 mm × 30 mm | for pantiles and double depression interlocking ti | 1.1 kg |
| 40970 | Brick-red | Powder-coated steel. | 450 mm × 210 mm × 30 mm | for pantiles and double depression interlocking ti | 1.2 kg |
| 40967 | brown | Powder-coated steel. | 450 mm × 210 mm × 30 mm | for pantiles and double depression interlocking ti | 1.2 kg |
| 41399 | Anthracite grey | Powder-coated steel. | 450 mm × 200 mm × 30 mm | for pantiles and double depression interlocking ti | 1.2 kg |
| 41386 | Steel, galvanised | Steel, galvanised | 430 mm × 190 mm × 30 mm | for plain tiles | 1 kg |
| 40492 | Copper-brown | Powder-coated steel. | 430 mm × 200 mm × 30 mm | for plain tiles | 1.2 kg |
| 41387 | Brick-red | Powder-coated steel. | 420 mm × 200 mm × 30 mm | for plain tiles | 1 kg |
| 41388 | brown | Powder-coated steel. | 430 mm × 190 mm × 30 mm | for plain tiles | 1 kg |
| 41389 | Anthracite grey | Powder-coated steel. | 430 mm × 190 mm × 30 mm | for plain tiles | 1 kg |