

# Mobile access steps with platform, double-sided access, with steel open-grid treads and platform

The flexible solution for wet-room applications, with open-grid treads for improved non-slip performance.

## Product description

- The flexible solution for wet-room applications, with open-grid treads for improved non-slip performance.
- Quick and easy assembly thanks to the new connecting elements.
- Mobile and quick to set up with four sprung swivel castors (two of which have brakes).
- Maximum safety through double-sided platform guardrail at a height of 1.00 m.
- Comfortable ascent thanks to 200 mm deep treads.
- Large platform, 600 x 800 mm.
- Maximum load 150 kg.

## Product features

Coating: natural  
 Connection between stiles and rungs/stiles: welded  
 Guardrail height: 1000 m  
 Load capacity: max. 150 kg  
 Material: Aluminum/steel, galvanised  
 Platform length: 800 mm  
 Platform width: 600 mm  
 Standards: EN 131-7  
 Tread depth: 200 mm  
 Type of rungs/treads: Open-grid surface  
 Vertical distance between each rung/tread: 240 mm  
 Warranty: 10 years



## Hints and special features

Optional double-sided handrail in compliance with DIN EN 131-7 on the steps.  
 For models prior to 2014, observe assembly instructions for sprung castors  
 Complies with EN 131-7

## Product variants

Order number	Base	Number of rungs, incl. platform	Number of treads	Platform height	Transport dimensions	Weight	Working height
41962	0,82 m × 1,79 m	2 × 4	4	0.96 m	1.960 mm × 830 mm × 300 mm	59.2 kg	2.95 m
41963	0,87 m × 2,06 m	2 × 5	5	1.2 m	1.850 mm × 890 mm × 460 mm	70.1 kg	3.2 m
41964	0,93 m × 2,34 m	2 × 6	6	1.44 m	2.140 mm × 930 mm × 380 mm	80.7 kg	3.45 m