

Multi-section fixed ladder systems, anodised aluminium

Multi-section access solution with crossover platform for buildings and machinery.

Product description

- For permanent mounting on buildings either for maintenance in accordance with DIN 18 799-1 or as an emergency ladder system in accordance with DIN 14 094-1 or as machine access steps in accordance with DIN EN ISO 14 122-4.
- With safety cage.
- Ladder width: 520 mm.
- Wall brackets with various wall clearances of up to 600 mm can be selected.
- The maximum permissible distance between two wall brackets is 2.00 m. But each ladder section must be mounted with at least two wall brackets.
- Safety barriers, access protection and platforms can be selected to suit individual requirements.
- We can also produce fixed-ladder designs that differ from the standard specification on request.

Product features

Material: Anodised aluminium
Warranty: 10 years

Product variants

| Order number | Overall length incl. stile | access height |
|--------------|----------------------------|---------------|
| 58507 | 11.8 m | 10.7 m |
| 58518 | 12.9 m | 11.8 m |
| 58526 | 13.7 m | 12.6 m |
| 58538 | 14.9 m | 13.8 m |
| 58549 | 16 m | 14.9 m |
| 58557 | 16.8 m | 15.7 m |
| 58568 | 17.9 m | 16.8 m |
| 58580 | 19.1 m | 18 m |
| 58591 | 20.2 m | 19.1 m |



to the product



Hints and special features

Dowels and screws/bolts for wall mounting are not included in the scope of delivery.
The prices for double-section systems listed below are calculated as follows: Wall bracket in the form of a U-bar, 200 mm rigid, straight stile extensions on both sides, crossover platform, incl. back cage in accordance with DIN 18 799-1. In the case of other requirements, please use our planning system for fixed ladders.