Mitraset Classic 19" housing

Housing for electronic instruments



Product description

- Protection against mechanical stresses such as impacts, shocks or vibrations. Protection against electromagnetic interference (such as radio waves or lightning strikes) is also available as an option.
- Protection against environmental influences such as heat, moisture, water or dust.
- For loads of up to 100 kg.
- 3 - 22 height units, nominal depth 219 - 990 mm.
- Housings with nominal depths 219 mm, 350 mm and 480 mm can be stacked together.
- Elastically susp. anti-vibration frame.
- Stacking segments on housing top and bottom.
- Recesses on side walls for drop handles.
- Recess also suitable for accommodating protective pressure compensation valves and humidity indicator.
- Standard housing with additional reinforced specifications.
- Lid with toggle-action snap fasteners.
- IP 65 rated
- Fulfils the requirements of VG 95447.
- Tested according to AECTP standards.
- Tested according to MIL-STD-810.
- Modified version with testing in accordance with MIL-STD-810 F.
- Shielding attenuation test in accordance with MIL-STD-285.
- Customised versions available.

Hints and special features

Additional sizes available on request. Height of casing with stacking foot = external dimension (nominal size) + 11.5mm. Depth of special lid varies according to design. Also available as UN-approved hazardous goods packaging.
A comprehensive range of special equipment for a wide variety of applications.

Product variants

Order number	Installation height	Nominal depth	Outside dimensions L x W x H	Weight
45702	3 HE/U	219 mm	303 mm × 534 mm × 214,5 mm	6.6 kg
45708	4 HE/U	219 mm	303 mm × 534 mm × 259 mm	7 kg
45714	5 HE/U	219 mm	303 mm × 534 mm × 303,5 mm	7.3 kg
45726	7 HE/U	219 mm	303 mm × 534 mm × 392,5 mm	7.8 kg
45720	6 HE/U	219 mm	303 mm × 534 mm × 348 mm	7.5 kg
45732	8 HE/U	219 mm	303 mm × 534 mm × 437 mm	8.2 kg
45738	9 HE/U	219 mm	303 mm × 534 mm × 481,5 mm	8.4 kg
45744	10 HE/U	219 mm	303 mm × 534 mm × 526 mm	8.6 kg
45750	11 HE/U	219 mm	303 mm × 534 mm × 570,5 mm	8.8 kg
45756	12 HE/U	219 mm	303 mm × 534 mm × 615 mm	9 kg
45704	3 HE/U	350 mm	434 mm × 534 mm × 214,5 mm	8.6 kg
45710	4 HE/U	350 mm	434 mm × 534 mm × 259 mm	9 kg
45716	5 HE/U	350 mm	434 mm × 534 mm × 303,5 mm	9.3 kg

ZARGES (U.K.) Ltd.
8 Holdom Avenue. Saxon Park Ind. Est.
Bletchley MK1 1QU
Tel: 01908 641118
Fax: 01908 641118
www.zarges.com
sales@zarges.co.uk

Order number	Installation height	Nominal depth	Outside dimensions L x W x H	Weight
45722	6 HE/U	350 mm	434 mm × 534 mm × 348 mm	9.6 kg
45728	7 HE/U	350 mm	434 mm × 534 mm × 348 mm	10 kg
45734	8 HE/U	350 mm	434 mm × 534 mm × 437 mm	10.3 kg
45740	9 HE/U	350 mm	434 mm × 534 mm × 481,5 mm	10.7 kg
45746	10 HE/U	350 mm	434 mm × 534 mm × 526 mm	11 kg
45752	11 HE/U	350 mm	434 mm × 534 mm × 570,5 mm	11.3 kg
45758	12 HE/U	350 mm	434 mm × 534 mm × 615 mm	11.6 kg
45706	3 HE/U	480 mm	564 mm × 534 mm × 214,5 mm	10.7 kg
45712	4 HE/U	480 mm	564 mm × 534 mm × 259 mm	11.1 kg
45718	5 HE/U	480 mm	564 mm × 534 mm × 303,5 mm	11.4 kg
45724	6 HE/U	480 mm	564 mm × 534 mm × 348 mm	11.9 kg
45730	7 HE/U	480 mm	564 mm × 534 mm × 392,5 mm	12.2 kg
45736	8 HE/U	480 mm	564 mm × 534 mm × 437 mm	12.6 kg
45742	9 HE/U	480 mm	564 mm × 534 mm × 481,5 mm	13 kg
45748	10 HE/U	480 mm	564 mm × 534 mm × 526 mm	13.3 kg
45754	11 HE/U	480 mm	564 mm × 534 mm × 570,5 mm	13.7 kg
45760	12 HE/U	480 mm	564 mm × 534 mm × 615 mm	14.1 kg
45803	3 HE/U	610 mm	704 mm × 534 mm × 214,5 mm	13.5 kg
45804	4 HE/U	610 mm	704 mm × 534 mm × 259 mm	14.1 kg
45805	5 HE/U	610 mm	704 mm × 534 mm × 303,5 mm	14.7 kg
45806	6 HE/U	610 mm	704 mm × 534 mm × 348 mm	15.2 kg
45807	7 HE/U	610 mm	704 mm × 534 mm × 392,5 mm	15.9 kg
45808	8 HE/U	610 mm	704 mm × 534 mm × 437 mm	16.6 kg
45809	9 HE/U	610 mm	704 mm × 534 mm × 481,5 mm	17.1 kg
45810	10 HE/U	610 mm	704 mm × 534 mm × 526 mm	17.5 kg
45811	11 HE/U	610 mm	704 mm × 534 mm × 570,5 mm	24.7 kg
45812	12 HE/U	610 mm	704 mm × 534 mm × 615 mm	18.6 kg
45814	14 HE/U	610 mm	704 mm × 534 mm × 704 mm	19.9 kg
45816	16 HE/U	610 mm	704 mm × 534 mm × 793 mm	
45863	3 HE/U	762 mm	856 mm × 534 mm × 214,5 mm	16.2 kg
45864	4 HE/U	762 mm	856 mm × 534 mm × 259 mm	16.8 kg
45865	5 HE/U	762 mm	856 mm × 534 mm × 303,5 mm	17.4 kg
45866	6 HE/U	762 mm	856 mm × 534 mm × 348 mm	17.9 kg
45867	7 HE/U	762 mm	856 mm × 534 mm × 392,5 mm	18.6 kg
45868	8 HE/U	762 mm	856 mm × 534 mm × 437 mm	19.3 kg
45869	9 HE/U	762 mm	856 mm × 534 mm × 481,5 mm	19.8 kg
45870	10 HE/U	762 mm	856 mm × 534 mm × 526 mm	20.2 kg
45871	11 HE/U	762 mm	856 mm × 534 mm × 570,5 mm	20.8 kg
45872	12 HE/U	762 mm	856 mm × 534 mm × 615 mm	21.3 kg
45874	14 HE/U	762 mm	856 mm × 534 mm × 704 mm	22 kg
45876	16 HE/U	762 mm	856 mm × 534 mm × 793 mm	23.8 kg
45878	18 HE/U	762 mm	856 mm × 534 mm × 882 mm	25.6 kg