

Lid for Mitraset Classic 19" housing

Product description

- Lid equipped with 4 toggle locks.
- Wide range of special lids available on request.
- Screw-down lids can also be supplied.
- Protection class IP 65 in accordance with DIN EN 60 60529 and IEC 34-5/529 through seam-welded housing and lid with peripheral seal.

Product variants

Order number	Height of lid	Outside dimensions L x W x H	Weight
45761	3 HE/U	63 mm × 534 mm × 214,5 mm	1.9 kg
45762	4 HE/U	63 mm × 534 mm × 259 mm	2.1 kg
45763	5 HE/U	63 mm × 534 mm × 303,5 mm	2.3 kg
45764	6 HE/U	63 mm × 534 mm × 348 mm	2.5 kg
45765	7 HE/U	63 mm × 534 mm × 392,5 mm	2.7 kg
45766	8 HE/U	63 mm × 534 mm × 437 mm	2.8 kg
45767	9 HE/U	63 mm × 534 mm × 481,5 mm	3 kg
45768	10 HE/U	63 mm × 534 mm × 526 mm	3.2 kg
45769	11 HE/U	63 mm × 534 mm × 570,5 mm	3.3 kg
45770	12 HE/U	63 mm × 534 mm × 615 mm	3.5 kg
45772	14 HE/U	63 mm × 534 mm × 704 mm	3.8 kg
45774	16 HE/U	63 mm × 534 mm × 793 mm	4.1 kg