Lid for Mitraset Racklite Basic 19" housing

Product description

- Protection class IP 65 in accordance with DIN EN 60 60529 and IEC 34-5/529 through seam-welded housing and lid with peripheral seal.
- Wide range of special lids available on request.
- Lid with ribbing for reinforcement.
- Lid equipped with 4 locking catches.

to the product

Product variants

Order number	Height of lid	Outside dimensions L x W x H	Weight
45983	3 HE/U	40 mm × 568 mm × 226 mm	1.8 kg
45984	4 HE/U	40 mm × 568 mm × 270,5 mm	2 kg
45985	5 HE/U	40 mm × 568 mm × 315 mm	2.2 kg
45986	6 HE/U	40 mm × 568 mm × 359,5 mm	2.3 kg
45987	7 HE/U	40 mm × 568 mm × 404 mm	2.5 kg
45988	8 HE/U	40 mm × 568 mm × 448,5 mm	2.7 kg
45989	9 HE/U	40 mm × 568 mm × 493 mm	2.9 kg
45990	10 HE/U	40 mm × 568 mm × 537,5 mm	3 kg
45991	11 HE/U	40 mm × 568 mm × 582 mm	3.2 kg
45992	12 HE/U	40 mm × 568 mm × 626,5 mm	3.4 kg

ZARGES (U.K.) Ltd.
8 Holdom Avenue. Saxon Park Ind. Est.
Bletchley MK1 1QU
Tel: 01908 641118
Fax: 01908 641118
www.zarges.com
sales@zarges.co.uk
Effective 3/29/2024
Errors and omissions excepted.