

R13step S

Safer ascent with the highest non-slip performance thanks to R13 treads for oily and wet conditions.

Product description

- Safer ascent with the highest non-slip performance thanks to R13 treads for oily and wet conditions.
- Large platform with R13 surface that allows personnel to stand safely and comfortably even when working for extended periods.
- Practical storage tray with plenty of space for tools and small parts.
- 80 mm deep treads with R13 surface and perforations to drain fluids fast.
- Wear-resistant, anodised stiles.
- Practical aluminium storage tray for small items and tools.
- Platform made from extruded aluminium (300 mm × 250 mm) with R13 surface for safer and comfortable standing even when working for longer periods of time.
- High-strength Perlon straps prevent splay, from 5 rungs.
- Maximum working height thanks to treads starting at 280 mm from the ground.
- Replaceable two-component plastic end caps that attach securely to the stile and prevent the ladder from slipping.



Hints and special features

Platform and treads with R13 surface.
Complies with EN 131 Professional.

Product features

Coating: anodised
 Connection between stiles and rungs/stiles: flanged
 Load capacity: max. 150 kg
 Material: aluminium
 Platform length: 250 mm
 Platform width: 300 mm
 Standards: EN 131 professional
 Stile depth: 73 mm
 Stile depth: 58 mm
 Stile depth steps/back stay: 73mm / 58mm
 Storage tray: aluminium
 Tread depth: 80 mm
 Type of rungs/treads: R13 tread
 Vertical distance between each rung/tread: 265 mm
 Warranty: 10 years

Product variants



Order number	Anti-splay mechanism	Base	Number of rungs, incl. platform	Overall base width	Overall length	Platform height	Transport dimensions
41636		0,57 m × 0,5 m	3	0.5 m	1.59 m	0.8 m	approx. 1.590 mm × approx. 500 mm × approx. 170 mm
41637		0,76 m × 0,53 m	4	0.53 m	1.87 m	1.06 m	approx. 1.870 mm × approx. 530 mm × approx. 170 mm
41638	Belt strap	0,96 m × 0,56 m	5	0.56 m	2.15 m	1.33 m	approx. 2.150 mm × approx. 560 mm × approx. 170 mm
41639	Belt strap	1,15 m × 0,59 m	6	0.59 m	2.43 m	1.59 m	approx. 2.430 mm × approx. 590 mm × approx. 170 mm
41640	Belt strap	1,34 m × 0,62 m	7	0.62 m	2.71 m	1.85 m	approx. 2.710 mm × approx. 620 mm × approx. 170 mm
41641	Belt strap	1,53 m × 0,65 m	8	0.65 m	2.99 m	2.12 m	approx. 2.990 mm × approx. 650 mm × approx. 170 mm
41642	Belt strap	1,91 m × 0,71 m	10	0.71 m	3.55 m	2.64 m	approx. 3.550 mm × approx. 710 mm × approx. 170 mm

Order number	Weight	Working height
41636	8.3 kg	2.8 m
41637	9.8 kg	3.1 m
41638	10.5 kg	3.35 m
41639	11.5 kg	3.6 m
41640	12.3 kg	3.85 m
41641	12.8 kg	4.15 m
41642	16.1 kg	4.65 m