

# Skymaster EFAmix X

The Skymaster is strong, sturdy and safely insulated thanks to glass reinforced polyester (GRP) stiles, making it ideal for working with electrical equipment or near electrical hazards.

## Product description

- The Skymaster is strong, sturdy and safely insulated thanks to glass reinforced polyester (GRP) stiles, making it ideal for working with electrical equipment or near electrical hazards.
- High level of protection provided for working on electrical installations thanks to insulated stiles made from glass-fire-reinforced plastic.
- One rigid locking bar.
- Aluminium rungs (30 x 30 mm).
- High-strength Perlon straps with sewn-in fixing tab to prevent splaying.
- Optimum wrap-around stile guide that encompasses the whole rung.
- Locks safely by means of rung hooks and locking tab.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.



to the product



## Hints and special features

Complies with EN 131 Professional.

## Product features

Connection between stiles and rungs/stiles: flanged  
 Ladder length as 3-part single ladder: 5.8 m  
 Length as 2-part single ladder and as stepladder with push-on section: 4.1 m  
 Load capacity: max. 150 kg  
 Material: Aluminium / plastic  
 Number of rungs: 8  
 Number of rungs: 3 × 8  
 Overall length, retracted: 2.45 m  
 Standards: EN 131 professional  
 Stile depth: 73 mm  
 Tread depth: 30 mm  
 Type of rungs/treads: serrated  
 Vertical distance between each rung/tread: 265 mm  
 Warranty: 10 years  
 Wide crosspiece: 1 m  
 Working height as 3-part single ladder: 6.55 m

## Product variants

Order  
 number  
 GRP41521