

Saferstep L

The high non-slip performance of Safer Step Technology makes for comfortable and safe use, while the anodised stiles are wear-resistant and pleasant to hold.

Product description

- The high non-slip performance of Safer Step Technology makes for comfortable and safe use, while the anodised stiles are wear-resistant and pleasant to hold.
- Also available as a shelf-ladder.
- Tread with ZARGES Safer Step Technology, 80 mm deep.
- Abrasion-resistant, anodised stiles.
- Overall width: 420 mm.
- High strength, non-twist rung/stile connections.
- Treads and stiles made from extruded aluminium sections.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



Coating: anodised Connection Stile-Rung: flanged Load capacity: max. 150 kg Material: Aluminium Pitch rung/tread: 265 mm Standards: EN 131 professional

Stile depth: 68 mm Tread depth: 80 mm Type rung/tread: Safer Step

Warranty: 10 years





Hints and special features

Complies with EN 131 Professional.

Product variants

Order number	Number of treads	Overall length	Transport dimensions	Weight	Wide crosspiece	Working height
41356	6	1.94 m	1.930 mm × 420 mm × 73 mm	5 kg		2.8 m
41358	8	2.5 m	2.490 mm × 420 mm × 73 mm	6.5 kg		3.35 m
41360	10	3.06 m	3.050 mm × 420 mm × 73 mm	8.8 kg	0.8 m	3.85 m
41362	12	3.62 m	3.610 mm × 420 mm × 73 mm	10.3 kg	0.8 m	4.4 m
41364	14	4.18 m	4.170 mm × 420 mm × 73 mm	11.8 kg	0.89 m	4.9 m
41366	16	4.74 m	4.730 mm × 420 mm × 73 mm	13.3 kg	0.89 m	5.45 m