

# Seventec L

The deep treads and 7-point tread-stile connection ensure a high degree of comfort, safe standing and extremely high stability.

## Product description

- Treads 85 mm deep and with safe, non-slip serrated surfaces.
- Smooth external stile surfaces that are comfortable to hold.
- Outside width: 400 mm.
- Especially light and easy to carry.
- 7-point connection between tread and stile with reinforcement in the centre of the tread.
- Treads and stiles made from extruded aluminium sections.
- Inside width: 360 mm.



## Product features

Coating: natural  
 Connection Stile-Rung: riveted  
 Load: max. 150 kg  
 Material: Aluminium  
 Pitch rung/tread: 218 mm  
 Producttype: Riveted single ladder with treads  
 Stile depth: 87 mm  
 Tread depth: 85 mm  
 Type rung/tread: serrated

## Hints and special features

in accordance with DIN EN 131-1, order No. 40384 includes a stabiliser bar.  
 Complies with EN 131 Professional.

## Product variants

Order number	Number of treads	Overall length	Transport dimensions	Weight	Wide crosspiece	Working height
40378	8	2.08 m	2.090 mm × 400 mm × 90 mm	5.8 kg		3.05 m
40380	10	2.54 m	2.550 mm × 400 mm × 90 mm	7.2 kg		3.45 m
40382	12	2.99 m	3.010 mm × 400 mm × 90 mm	8.5 kg		3.9 m
40384	14	3.42 m	3.470 mm × 400 mm × 90 mm	11.4 kg	0.8 m	4.35 m