

Seventec L - 40382

The deep treads and 7-point tread-stile connection ensure a high degree of comfort, safe standing and extremely high stability.

Product description

- The deep treads and 7-point tread-stile connection ensure a high degree of comfort, safe standing and extremely high stability.
- Smooth external stile surfaces that are comfortable to hold.
- Treads 85 mm deep and with safe, non-slip serrated surfaces.
- Outside width: 400 mm.
- Especially light and easy to carry.
- 7-point connection between tread and stile with reinforcement in the centre of the tread.
- Treads and stiles made from extruded aluminium sections.
- Inside width: 360 mm.



Product features

Coating: natural
 Connection Stile-Rung: riveted
 Load capacity: max. 150 kg
 Material: Aluminium
 Number of treads: 12
 Overall length: 2.99 m
 Pitch rung/tread: 218 mm
 Standards: EN 131 professional
 Stile depth: 87 mm
 Transport dimensions: 3.010 mm × 400 mm × 90 mm
 Tread depth: 85 mm
 Type rung/tread: serrated
 Warranty: 10 years
 Weight: 8.5 kg
 Working height: 3.9 m

Hints and special features

in accordance with DIN EN 131-1, order No. 40384
 includes a stabiliser bar.
 Complies with EN 131 Professional.

Accessories and spare parts

Image	Order number	Name	Type
	40920	Hook-on tool box	Accessory
	40300	Toolbag	Accessory
	40998	Ladder holder, lockable	Accessory
	40960	Tension strap	Accessory
	40250	Ladder stay / base	Parts list



Image	Order number	Name	Type
		stabiliser	
	40999	Gutter fastening	Parts list
	800288	Push-on end cap	Spare part
	800289	Push-on end cap	Spare part