Strato DL

The inexpensive alternative for safe ascent and quick and flexible application.





Product description

- The inexpensive alternative for safe ascent and quick and flexible application.
- Robust extruded-section triangular rungs with step horizontal in working position.
- Outside width: 350 mm.
- Special rung design creates a broad step area.
- Stiles made from extruded aluminium sections for maximum stability.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.
- High strength, non-twist rung/stile connections.

Product features

Coating: natural
Connection Stile-Rung: flanged
Load capacity: max. 150 kg
Material: Aluminium
Pitch rung/tread: 265 mm
Standards: EN 131 professional
Tread depth: 38 mm
Type rung/tread: serrated
Warranty: 10 years

Hints and special features

Complies with EN 131 Professional.

Product variants

Order number	Number of rungs	Overall length	Stile depth	Transport dimensions	Weight	Wide crosspiece	Working height
44808	8	2.42 m	58 mm	2.420 mm × 360 mm × 60 mm	4.3 kg		3.3 m
44810	10	2.98 m	58 mm	2.980 mm × 360 mm × 60 mm	5.3 kg		3.85 m
44812	12	3.54 m	68 mm	3.540 mm × 360 mm × 70 mm	7.9 kg	0.79 m	4.4 m
44814	14	4.11 m	73 mm	4.110 mm × 360 mm × 75 mm	9.2 kg	0.79 m	4.9 m
44816	16	4.67 m	73 mm	4.660 mm × 360 mm × 75 mm	10.1 kg	0.89 m	5.45 m
44818	18	5.23 m	73 mm	5.220 mm × 360 mm × 75 mm	11.2 kg	0.89 m	6 m
44819	20	5.9 m	73 mm	5.780 mm × 360 mm × 75 mm	12.4 kg	0.99 m	6.55 m

ZARGES GmbH
Zargesstraße 7
D-82362 Weilheim
Tel: +49 (0)881-687-0
Fax: +49 (0)881-687-0
www.zarges.com
international-sales@zarges.de