

Comfortstep LH

These flexible ladders ensure safe access to shelving and can be adapted to the required height.

Product description

- These flexible ladders ensure safe access to shelving and can be adapted to the required height.
- Hook-on shelf ladders have two hooks for the guide rail and additional hooks for vertical storage on the shelf.

Product features

Coating: anodised Connection Stile-Rung: bolted Load capacity: max. 150 kg Material: Aluminium Pitch rung/tread: 250 mm Standards: EN 131 professional

Tread depth: 80 mm

Type rung/tread: padding on front tread edges

Warranty: 10 years



Hints and special features

Please quote the distance between the floor and the top edge of the tubular rail when ordering! Complies with EN 131 Professional.

Product variants

Order number	Height hook on vertical	Max height hook on vertical	Min height hook on vertical	Number of treads	Transport dimensions	Weight	Working height
41402	=1,45m-=1,69 m	1.69 m	1.45 m	6	1.660 mm × 380 mm × 100 mm	4.5 kg	2.75 m
41403	=1,7m-=1,94 m	1.94 m	1.7 m	7	1.900 mm × 380 mm × 100 mm	5.2 kg	3 m
41404	=1,95m-=2,19 m	2.19 m	1.95 m	8	2.140 mm × 380 mm × 100 mm	5.9 kg	3.25 m
41405	=2,2m-=2,44 m	2.44 m	2.2 m	9	2.380 mm × 380 mm × 140 mm	6.6 kg	3.5 m
41406	=2,45m-=2,69 m	2.69 m	2.45 m	10	2.300 mm × 380 mm × 150 mm	7.3 kg	3.75 m