

Comfortstep Trec LH

For easy travel backwards and forwards along your shelving: The solution with guide rails and self-locking sprung castors is individually height-adjustable.

Product description

- For easy travel backwards and forwards along your shelving: The solution with guide rails and self-locking sprung castors is individually height-adjustable.
- Both the top of the ladder and the self-locking sprung castors at the bottom lock the shelf ladder when weight is applied.
- When not in use, the ladder can be stowed vertically on the shelf to save space.

Product features

Coating: anodised
 Connection Stile-Rung: bolted
 Load capacity: max. 150 kg
 Material: Aluminium
 Pitch rung/tread: 250 mm
 Standards: EN 131 professional
 Tread depth: 80 mm
 Type rung/tread: padding on front tread edges
 Warranty: 10 years



Hints and special features

Please quote the distance between the floor and the top edge of the tubular rail when ordering!
 Complies with EN 131 Professional.

Product variants

Order number	Height hook on vertical	Max height hook on vertical	Min height hook on vertical	Number of treads	Transport dimensions	Weight	Working height
41412	=1,84m-≈2,08 m	2.08 m	1.84 m	6	1.680 mm × 380 mm × 100 mm	4.5 kg	2.75 m
41413	=2,09m-≈2,33 m	2.33 m	2.09 m	7	1.920 mm × 380 mm × 100 mm	5.2 kg	3 m
41414	=2,34m-≈2,58 m	2.58 m	2.34 m	8	2.160 mm × 380 mm × 100 mm	5.9 kg	3.25 m
41415	=2,59m-≈2,83 m	2.83 m	2.59 m	9	2.400 mm × 380 mm × 100 mm	6.6 kg	3.5 m
41416	=2,84m-≈3,08 m	3.08 m	2.84 m	10	2.640 mm × 380 mm × 100 mm	7.6 kg	3.75 m