

Saferstep Trec LH

For easy travel backwards and forwards along your shelving: The solution with guide rails and self-locking sprung castors at the bottom lock the shelf ladder when weight is applied.

Product description

- Both the top of the ladder and the self-locking sprung castors at the bottom lock the shelf ladder when weight is applied.
- When not in use, the ladder can be stowed vertically on the shelf to save space.

Product features

Coating: anodised
 Connection Stile-Rung: flanged
 Load: max. 150 kg
 Material: Aluminium
 Pitch rung/tread: 265 mm
 Producttype: Flanged mobile shelf ladder with treads
 Tread depth: 80 mm
 Type rung/tread: Safer Step

Product variants

Order number	Height hook on vertical	Max height hook on vertical	Min height hook on vertical	Number of treads	Transport dimensions
1141356	=1,67m-=2,16 m	= 2.16 m	= 1.67 m	6	2.350 mm × 423 mm × 73 mm
1141358	=2,17m-=2,67 m	= 2.67 m	= 2.17 m	8	2.910 mm × 423 mm × 73 mm
1141360	=2,68m-=3,2 m	= 3.2 m	= 2.68 m	10	3.470 mm × 423 mm × 73 mm
1141362	=3,21m-=3,72 m	= 3.72 m	= 3.21 m	12	4.030 mm × 423 mm × 73 mm
1141364	=3,73m-=4,25 m	= 4.25 m	= 3.73 m	14	4.590 mm × 423 mm × 73 mm



Hints and special features

Please quote the distance between the floor and the top edge of the tubular rail when ordering!
 Complies with EN 131 Professional.