

Everest 2DE

Safe, flexible and suitable for great heights, with an excellent price/performance ratio.

Product description

- Safe, flexible and suitable for great heights, with an excellent price/performance ratio.
- Convenient and precise rung-by-rung height adjustment in a grid of 280 mm.
- Both parts of the ladder can also be used separately as single ladders for Order Nos. 44834 and 44820
- Robust extruded-section triangular rungs with step horizontal in working position.
- External width of lower ladder: 420 mm.
- Positive-locking extruded aluminium section guide fittings.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



Product features

Coating: natural
 Connection Stile-Rung: flanged
 External width of lower ladder: 420 mm
 Load capacity: max. 150 kg
 Material: Aluminium
 Pitch rung/tread: 265 mm
 Standards: EN 131 professional
 Tread depth: 38 mm
 Type rung/tread: serrated
 Warranty: 10 years

Hints and special features

Complies with EN 131 Professional.

Product variants

Order number	Number of rungs	Number of rungs	Overall length, extended	Overall length, retracted	Stile depth	Transport dimensions	Weight
44834	8	2 × 8	3.8 m	2.42 m	58 mm	2.420 mm × 420 mm × 115 mm	9.3 kg
44820	10	2 × 10	4.93 m	2.98 m	68 mm	2.980 mm × 430 mm × 120 mm	11.3 kg
44822	12	2 × 12	6.05 m	3.54 m	68 mm	3.540 mm × 430 mm × 135 mm	15.4 kg
44824	14	2 × 14	7.17 m	4.1 m	85 mm	4.100 mm × 430 mm × 135 mm	17.8 kg
44826	16	2 × 16	8.29 m	4.66 m	85 mm	4.660 mm × 430 mm × 145 mm	21.5 kg
44828	18	2 × 18	9.17 m	5.23 m	85 mm	5.230 mm × 430 mm × 145 mm	23.9 kg

Order number	Wide crosspiece	Working height
44834	0.8 m	4.6 m
44820	0.9 m	5.65 m
44822	1 m	6.8 m



Order number	Wide crosspiece	Working height
--------------	-----------------	----------------

44824	1.1 m	7.85 m
-------	-------	--------

44826	1.2 m	8.7 m
-------	-------	-------

44828	1.2 m	9.8 m
-------	-------	-------