

## Everest EFA 2E

Plastic ladder for access to great heights, for use in electrical and chemical environments.

### Product description

- Stiles and rungs (30 mm x 30 mm) made from glass-fibre-reinforced plastic for particularly high chemical resistance.
- Convenient and precise rung-by-rung height adjustment in a grid of 280 mm.
- Both parts of the ladder can also be used separately as single ladders for Order Nos. 41288-41290.
- Complies with the high-voltage test for ladders of insulating material in accordance with DIN EN 61 478 or VDE 0682 Section 6.5 Category 1/30 KV.
- Suitable for working in high-voltage environments (1000 V AC, 1500 V DC).
- Overall width of bottom section: 430 mm.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



### Product features

Ext. width: 420 mm  
 External width of lower ladder: 420 mm  
 Load: max. 150 kg  
 Material: Glass-fibre reinforced plastic  
 Number ladderparts: 2  
 Pitch rung/tread: 270 mm  
 Producttype: GRP push-up ladder with rungs, 2-section  
 Tread depth: 30 mm  
 Type rung/tread: serrated

### Product variants

Order number	Number of rungs	Number of rungs	Overall length, extended	Overall length, retracted	Transport dimensions	Weight	Wide crosspiece	Working height
41288	8	2 × 8	4.17 m	2.44 m	2.500 mm × 430 mm × 125 mm	14.3 kg	0.8 m	4.95 m
41290	10	2 × 10	4.91 m	2.95 m	2.950 mm × 430 mm × 150 mm	19.5 kg	0.9 m	5.7 m
41292	12	2 × 12	6.03 m	3.51 m	3.510 mm × 430 mm × 150 mm	23.3 kg	1 m	6.75 m