

Skyline 2E

Easy and convenient vertical height adjustment makes this ladder ideal for use to access very great heights.

Product description

- A high level of stability thanks to extra-wide bottom ladder (490 mm).
- Very easy and convenient rung-by-rung height adjustment in a 280 mm grid via synthetic rope and roller.
- Locks securely thanks to automatic spring loaded pawls.
- Top ladder section fitted with wall wheels.
- Wheel assemblies with abrasion-resistant surfaces that will not damage the wall.
- High strength, non-twist rung/stile connections.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



Product features

Coating: natural
 Connection Stile-Rung: flanged
 Ext. width: 490 mm
 External width of lower ladder: 490 mm
 Load: max. 150 kg
 Material: Aluminium
 Number ladderparts: 2
 Pitch rung/tread: 270 mm
 Producttype: Flanged rope-operated ladder with rungs, 2-section
 Tread depth: 30 mm
 Type rung/tread: serrated
 Wheels: Rubber
 Wide crosspiece: 1.2 m

Hints and special features

Convenient rung-by-rung height adjustment, with wall wheels that will not damage the wall.

Product variants

Order number	Number of rungs	Number of rungs	Overall length, extended	Overall length, retracted	Stile depth	Transport dimensions	Weight	Working height
40206	14	2 × 14	7.21 m	4.14 m	73mm	4.133 mm × 521 mm × 173 mm	22.821 kg	7.9 m
40207	16	2 × 16	8.33 m	4.7 m	98mm	4.696 mm × 520 mm × 184 mm	24.723 kg	9 m
40208	18	2 × 18	9.13 m	5.2 m	98mm	5.178 mm × 521 mm × 214 mm	30.929 kg	9.75 m
40209	20	2 × 20	10.25 m	5.74 m	114mm	5.717 mm × 521	33.832	10.85 m

Order number	Number of rungs	Number of rungs	Overall length, extended	Overall length, retracted	Stile depth	Transport dimensions	Weight	Working height
						mm × 198 mm	kg	
40212	22	2 × 22	11.1 m	6.4 m	114mm	6.394 mm × 521 mm × 214 mm	37.936 kg	11.7 m
40210	24	2 × 24	12.22 m	6.9 m	114mm	6.894 mm × 521 mm × 214 mm	42.641 kg	12.75 m