

Skyline EFA 2E

For special applications at great heights: the special ladder for working in high-voltage or chemical environments, with convenient height adjustment.

Product description

- For special applications at great heights: the special ladder for working in high-voltage or chemical environments, with convenient height adjustment.
- Stiles and rungs made of glass-fibre-reinforced plastic for particularly high chemical resistance.
- Complies with the high-voltage test for ladders of insulating material in accordance with DIN EN 61 478 or VDE 0682 Section 6.5 Category 1/30 KV.
- Suitable for working in high-voltage environments (1000 V AC, 1500 V DC).
- Very easy and convenient rung-by-rung height adjustment in a 280 mm grid via synthetic rope and roller.
- Wall wheels that will not damage the wall.
- Stiles and rungs (30 mm x 30 mm) made from glass-fibre-reinforced plastic for particularly high chemical resistance.
- Resistance to ageing in accordance with DIN EN ISO 4892-2.
- Overall width of bottom section: 430 mm.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



Hints and special features

Complies with EN 131 Professional.

Product features

External width of lower ladder: 420 mm
 Load capacity: max. 150 kg
 Material: Glass-fibre reinforced plastic
 Pitch rung/tread: 270 mm
 Standards: EN 131 professional
 Stile depth: 90 mm
 Tread depth: 30 mm
 Type rung/tread: serrated
 Warranty: 10 years
 Wheels: Rubber

Product variants

Order number	Number of rungs	Number of rungs	Overall length, extended	Overall length, retracted	Transport dimensions	Weight	Wide crosspiece
41274	14	2 x 14	7.17 m	4.09 m	4.100 mm x 470 mm x 150 mm	35.7 kg	1.1 m
41276	16	2 x 16	7.72 m	4.64 m	4.650 mm x 450 mm x 150 mm	41.3 kg	1.2 m



Order number	Working height
-----------------	----------------

41274	7.95 m
-------	--------

41276	8.5 m
-------	-------