

# XLstep S

Low weight, simple handling and a good price/performance ratio with high-value equipment.

## Product description

- Low weight, simple handling and a good price/performance ratio with high-value equipment.
- Stand without fatigue on deep treads.
- Large platform that allows personnel to stand safely and comfortably even when working for extended periods.
- Treads with a depth of 80 mm for fatigue-free standing.
- Abrasion-resistant, anodised stiles.
- Platform made from extruded aluminium (300 mm × 250 mm) for safe and comfortable standing even when working for longer periods of time.
- Spacious aluminium storage tray for material and tools.
- High-strength Perlon belts prevent splay, fitted on all models of 4 rungs or more.
- Triple-riveted connection between treads and stiles.
- Non-slip plastic end caps.
- Treads and stiles made from extruded aluminium sections.



## Hints and special features

Complies with EN 131 Professional.

## Product features

Coating: anodised  
 Connection Stile-Rung: riveted  
 Load capacity: max. 150 kg  
 Material: Aluminium  
 Pitch rung/tread: 250 mm  
 Platform length: 250 mm  
 Platform width: 300 mm  
 Standards: EN 131 professional  
 Stile depth: 42 mm  
 Tray: Aluminium  
 Tread depth: 80 mm  
 Type rung/tread: serrated  
 Warranty: 10 years

## Product variants

Order number	Anti splay	Base	Number of rungs, incl. platform	Overall base width	Overall length	Platform height	Stile depth
41223		0,74 m × 0,49 m	3	0,49 m	1,56 m	0,74 m	42 mm
41224	Belt strap	0,91 m × 0,52 m	4	0,52 m	1,83 m	0,99 m	42 mm
41225	Belt strap	1,08 m × 0,55 m	5	0,55 m	2,1 m	1,24 m	42 mm

Order number	Anti splay	Base	Number of rungs, incl. platform	Overall base width	Overall length	Platform height	Stile depth
41226	Belt strap	1,25 m × 0,57 m	6	0.57 m	2.37 m	1.49 m	48 mm
41227	Belt strap	1,42 m × 0,61 m	7	0.61 m	2.64 m	1.74 m	48 mm
41228	Belt strap	1,59 m × 0,63 m	8	0.63 m	2.91 m	1.99 m	48 mm
41230	Belt strap	1,93 m × 0,69 m	10	0.69 m	3.45 m	2.49 m	48 mm

Order number	Stile depth steps/back stay	Transport dimensions	Vertical ladder height	Weight	Working height
41223	42mm / 42mm	approx. 1.560 mm × approx. 490 mm × approx. 155 mm	1.42 m	6 kg	2.75 m
41224	42mm / 42mm	approx. 1.830 mm × approx. 520 mm × approx. 155 mm	1.67 m	6.9 kg	3 m
41225	42mm / 42mm	approx. 2.100 mm × approx. 550 mm × approx. 155 mm	1.92 m	7.7 kg	3.25 m
41226	48mm / 42mm	approx. 2.370 mm × approx. 570 mm × approx. 155 mm	2.17 m	9.1 kg	3.5 m
41227	48mm / 42mm	approx. 2.640 mm × approx. 610 mm × approx. 155 mm	2.42 m	10.2 kg	3.75 m
41228	48mm / 42mm	approx. 2.910 mm × approx. 630 mm × approx. 155 mm	2.67 m	11.7 kg	4 m
41230	48mm / 42mm	approx. 3.450 mm × approx. 690 mm × approx. 155 mm	3.17 m	14.1 kg	4.5 m