Scana S

High degree of comfort while working due to abrasion-resistant, anodised stiles and large storage tray.







Product description

- High degree of comfort while working due to abrasion-resistant, anodised stiles and large storage tray.
- Large platform with anti-slip ribbing.
- Tread depth 80 mm.
- Abrasion-resistant, anodised stiles.
- Practical tray with plenty of space for tools and small items.
- High-strength Perlon belts prevent splay from 6 rungs.
- The extruded aluminium sections give the platform optimum stability.
- Two extruded section bridge raisers.

Product features

Coating: anodised
Connection Stile-Rung: riveted
Load capacity: max. 150 kg
Material: Aluminium
Pitch rung/tread: 216 mm
Platform length: 250 mm
Platform width: 250 mm
Standards: EN 131 professional
Stile depth: 40 mm
Stile depth: 40 mm
Stile depth steps/back stay: 40mm / 40mm
Tray: Plastic
Tread depth: 80 mm
Type rung/tread: serrated
Warranty: 10 years

Hints and special features

Complies with EN 131 Professional.

Product variants

Order number	Anti splay	Base	Number of rungs, incl. platform	Overall base width	Overall length	Platform height	Transport dimensions
44153		0,67 m × 0,41 m	3	0.41 m	1.36 m	0.59 m	1.370 mm × 410 mm × 110 mm
44154		0,82 m × 0,43 m	4	0.43 m	1.59 m	0.81 m	1.600 mm × 440 mm × 110 mm
44155		0,96 m × 0,46 m	5	0.46 m	1.82 m	1.03 m	1.830 mm × 460 mm × 110 mm
44156	Belt strap	1,1 m × 0,48 m	6	0.48 m	2.05 m	1.24 m	2.060 mm × 490 mm × 110 mm
44157	Belt strap	1,25 m × 0,51 m	7	0.51 m	2.29 m	1.47 m	2.290 mm × 510 mm × 110 mm
44158	Belt strap	1,7 m × 0,53 m	8	0.53 m	2.52 m	1.7 m	2.520 mm × 530 mm × 110 mm

Order number	Vertical ladder height	Weight	Working height
44153	1.2 m	3.7 kg	2.6 m
44154	1.42 m	4.4 kg	2.8 m
44155	1.64 m	5.1 kg	3 m
44156	1.85 m	5.9 kg	3.25 m
44157	2.08 m	6.6 kg	3.5 m
44158	2.31 m	8 kg	3.7 m