



## EFAmix S

The special ladders for all applications in electrical environments.

### Product description

- Aluminium alloy treads, 80 mm deep, with non-slip serrated surface.
- Can be used for work on electrical installations, thanks to insulating stiles made from glass-fibre-reinforced plastic.
- Safety platform (250 x 250 mm).
- Safe storage of accessories and tools in an aluminium storage tray.
- Only 88 mm wide when folded.
- Complies with the high-voltage test for ladders of insulating material in accordance with DIN EN 61 478.
- Treads made from extruded aluminium section.



### Product features

Anti splay: Belt strap  
 Connection Stile-Rung: flanged  
 Length as work platform: 250 mm  
 Load: max. 150 kg  
 Material: Aluminium / plastic  
 Pitch rung/tread: 230 mm  
 Platform width: 250 mm  
 Producttype: GRP composite stepladder with treads  
 Stile depth: 50 mm  
 Stile depth: 50 mm  
 Stile depth steps/back stay: 50mm / 50mm  
 Tray: Plastic  
 Tread depth: 80 mm  
 Type rung/tread: serrated

### Hints and special features

Complies with EN 131 Professional.

### Product variants

Order number	Base	Number of rungs, incl. platform	Overall base width	Overall length	Platform height	Transport dimensions	Weight	Working height
40431	0,75 m × 0,52 m	3	0.52 m	1.4 m	0.68 m	1.390 mm × approx. 520 mm × 100 mm	6 kg	2.7 m
40432	0,91 m × 0,55 m	4	0.55 m	1.65 m	0.91 m	1.640 mm × approx. 550 mm × 100 mm	7 kg	2.9 m
40433	1,07 m × 0,57 m	5	0.57 m	1.9 m	1.14 m	1.890 mm × approx. 570 mm × 100 mm	8 kg	3.15 m



Order number	Base	Number of rungs, incl. platform	Overall base width	Overall length	Platform height	Transport dimensions	Weight	Working height
40434	1,24 m × 0,6 m	6	0.6 m	2.15 m	1.37 m	2.140 mm × approx. 600 mm × 100 mm	9 kg	3.35 m
40435	1,4 m × 0,62 m	7	0.62 m	2.4 m	1.6 m	2.390 mm × approx. 620 mm × 100 mm	10 kg	3.6 m