Saferstep B

The comfort version for flexible application, with high safety due to the use of Safer Step Technology and pleasant to grip.



Product description

- The comfort version for flexible application, with high safety due to the use of Safer Step Technology and pleasant to grip.
- Tread with ZARGES Safer Step Technology, 80 mm deep.
- Abrasion-resistant, anodised stiles.
- Hinges of diecast aluminium.
- High-strength perlon belts prevent splay.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.
- Maximum working heights thanks to 280mm high access.





Product features

Anti splay: Belt strap
Coating: anodised
Connection Stile-Rung: flanged
Load capacity: max. 150 kg
Material: Aluminium
Pitch rung/tread: 265 mm
Standards: EN 131 professional
Stile depth: 68 mm
Tread depth: 80 mm
Type rung/tread: Safer Step
Warranty: 10 years

Hints and special features

Complies with EN 131 Professional.

Product variants

Order number	Base	Number of treads	Number of treads	Overall base width	Overall length	Transport dimensions	Vertical ladder height
41303	0,8 m × 0,44 m	3	2 × 3	0.44 m	0.88 m	875 mm × 445 mm × 230 mm	0.8 m
41304	0,99 m × 0,47 m	4	2 × 4	0.47 m	1.15 m	1.153 mm × 475 mm × 230 mm	1.06 m
41305	1,18 m × 0,5 m	5	2 × 5	0.5 m	1.42 m	1.425 mm × 505 mm × 230 mm	1.32 m
41306	1,38 m × 0,53 m	6	2 × 6	0.53 m	1.7 m	1.705 mm × 535 mm × 230 mm	1.58 m
41307	1,58 m × 0,56 m	7	2 × 7	0.56 m	1.98 m	1.985 mm × 565 mm × 230 mm	1.84 m
41308	1,77 m × 0,59 m	8	2 × 8	0.59 m	2.27 m	2.275 mm × 595 mm × 230 mm	2.1 m
41310	2,16 m × 0,65 m	10	2 × 10	0.65 m	2.83 m	2.835 mm × 655 mm × 230 mm	2.62 m
41312	2,55 m × 0,71 m	12	2 × 12	0.71 m	3.39 m	3.390 mm × 715 mm × 230 mm	3.15 m
41314	2,95 m × 0,77 m	14	2 × 14	0.77 m	3.95 m	3.950 mm × 775 mm × 230 mm	3.67 m
41316	3,34 m × 0,83 m	16	2 × 16	0.83 m	4.51 m	4.510 mm × 830 mm × 230 mm	4.21 m

Order number	Weight	Working height
41303	4.6 kg	2.3 m
41304	6.1 kg	2.55 m
41305	7.6 kg	2.8 m
41306	9.3 kg	3.05 m
41307	10.9 kg	3.3 m
41308	12.7 kg	3.6 m
41310	16.4 kg	4.15 m
41312	20.3 kg	4.65 m
41314	24.4 kg	5.2 m
41316	28.8 kg	5.7 m