

Comfortstep B

Shin protection during ascent and descent and attractive design ensure high comfort when working and a flexible range of applications.

Product description

- 80 mm deep treads with padded front edges.
- Abrasion-resistant, anodised stiles.
- High-strength perlon belts prevent splay.
- Treads with plastic-cushioned front edges.
- Non-slip plastic end caps.
- Treads and stiles made from extruded aluminium sections.
- Screwed connection between treads and stile.



Product features

Anti splay: Belt strap
 Coating: anodised
 Connection Stile-Rung: bolted
 Load: max. 150 kg
 Material: Aluminium
 Pitch rung/tread: 250 mm
 Producttype: Bolted stepladder with treads
 Tread depth: 80 mm
 Type rung/tread: padding on front tread edges



Hints and special features

Maximum comfort due to padded treads.
 Complies with EN 131 Professional.

Product variants

Order number	Base	Number of treads	Number of treads	Overall base width	Overall length	Stile depth	Transport dimensions	Vertical ladder height	Weight	Working height
41432	0,74 m × 0,44 m	3	2 × 3	0,44 m	0,84 m	42 mm	840 mm × 445 mm × 174 mm	0,75 m	4,4 kg	2,25 m
41433	0,95 m × 0,47 m	4	2 × 4	0,47 m	1,11 m	42 mm	1,110 mm × 470 mm × 174 mm	1 m	5,8 kg	2,5 m
41434	1,15 m × 0,5 m	5	2 × 5	0,5 m	1,38 m	42 mm	1,380 mm × 500 mm × 174 mm	1,25 m	7,3 kg	2,75 m
41435	1,35 m × 0,53 m	6	2 × 6	0,53 m	1,65 m	42 mm	1,650 mm × 530 mm × 174 mm	1,5 m	8,8 kg	3 m
41436	1,55 m × 0,56 m	7	2 × 7	0,56 m	1,92 m	42 mm	1,920 mm × 560 mm × 174 mm	1,75 m	10,3 kg	3,25 m
41437	1,75 m × 0,59 m	8	2 × 8	0,59 m	2,18 m	48 mm	2,185 mm × 590 mm × 174 mm	2 m	12,2 kg	3,5 m
41438	2,16 m × 0,65 m	10	2 × 10	0,65 m	2,72 m	48 mm	2,725 mm × 650 mm × 174 mm	2,5 m	15,8 kg	4 m
41430	2,36 m × 0,68 m	11	2 × 11	0,68 m	2,99 m	48 mm	3,000 mm × 680 mm × 174 mm	2,75 m	17,6 kg	4,25 m