



XLstep B

Low weight and optimum price/performance ratio without compromising on comfort or equipment.

Product description

- Treads with a depth of 80 mm for fatigue-free standing.
- Abrasion-resistant, anodised stiles.
- High-strength perlon belts prevent splay.
- Triple-riveted connection between treads and stiles.
- Treads and stiles made from extruded aluminium sections.



Product features

Anti splay: Belt strap

Coating: anodised

Connection Stile-Rung: riveted

Load: max. 150 kg

Material: Aluminium

Pitch rung/tread: 250 mm

Producttype: Riveted stepladder with treads

Tread depth: 80 mm

Type rung/tread: serrated



Hints and special features

Complies with EN 131 Professional.

Product variants

Order number	Base	Number of treads	Number of treads	Overall base width	Overall length	Stile depth	Transport dimensions	Vertical ladder height	Weight	Working height
41263	0,72 m × 0,44 m	3	2 × 3	0,44 m	0,82 m	42 mm	820 mm × 440 mm × 170 mm	0,74 m	2,6 kg	2,25 m
41264	0,92 m × 0,47 m	4	2 × 4	0,47 m	1,09 m	42 mm	1,090 mm × 470 mm × 170 mm	0,99 m	3,4 kg	2,5 m
41265	1,12 m × 0,5 m	5	2 × 5	0,5 m	1,36 m	42 mm	1,360 mm × 500 mm × 170 mm	1,24 m	4,5 kg	2,75 m
41266	1,32 m × 0,53 m	6	2 × 6	0,53 m	1,63 m	42 mm	1,630 mm × 530 mm × 170 mm	1,49 m	6,1 kg	3 m
41267	1,54 m × 0,56 m	7	2 × 7	0,56 m	1,9 m	48 mm	1,900 mm × 560 mm × 170 mm	1,74 m	8,3 kg	3,25 m
41268	1,74 m × 0,59 m	8	2 × 8	0,59 m	2,17 m	48 mm	2,170 mm × 590 mm × 170 mm	1,99 m	11,3 kg	3,5 m
41270	2,15 m × 0,64 m	10	2 × 10	0,64 m	2,71 m	48 mm	2,710 mm × 640 mm × 170 mm	2,49 m	15,8 kg	4 m