

# Scana B

Flexible working and pleasant to handle due to the anodised stiles.

## Product description

- Tread depth 80 mm.
- Abrasion-resistant, anodised stiles.
- High-strength perlon belts prevent splay.

## Product features

Anti splay: Belt strap  
 Coating: anodised  
 Connection Stile-Rung: riveted  
 Load: max. 150 kg  
 Material: Aluminium  
 Pitch rung/tread: 216 mm  
 Producttype: Riveted stepladder with treads  
 Stile depth: 40 mm  
 Tread depth: 80 mm  
 Type rung/tread: serrated



## Hints and special features

Complies with EN 131 Professional.

## Product variants

Order number	Base	Number of treads	Number of treads	Overall base width	Overall length	Transport dimensions	Vertical ladder height	Weight	Working height
44203	0,59 m × 0,43 m	3	2 × 3	0.43 m	0.71 m	710 mm × 430 mm × 160 mm	0.66 m	3 kg	2.2 m
44204	0,76 m × 0,45 m	4	2 × 4	0.45 m	0.94 m	940 mm × 460 mm × 160 mm	0.87 m	3.8 kg	2.45 m
44205	0,91 m × 0,48 m	5	2 × 5	0.48 m	1.17 m	1.170 mm × 480 mm × 160 mm	1.09 m	4.8 kg	2.65 m
44206	1,1 m × 0,5 m	6	2 × 6	0.5 m	1.4 m	1.400 mm × 500 mm × 160 mm	1.3 m	5.8 kg	2.85 m
44207	1,28 m × 0,52 m	7	2 × 7	0.52 m	1.66 m	1.630 mm × 530 mm × 160 mm	1.52 m	6.8 kg	3.1 m