# Scana B - 44205

Flexible working and pleasant to handle due to the anodised stiles.



## Product description

- Flexible working and pleasant to handle due to the anodised stiles.
- Tread depth 80 mm.
- Abrasion-resistant, anodised stiles.
- High-strength perlon belts prevent splay.

## Product features

Anti splay: Belt strap
Base: 0,91 m × 0,48 m
Coating: anodised
Connection Stile-Rung: riveted
Load capacity: max. 150 kg
Material: Aluminium
Number of treads: 5
Number of treads: 2 × 5
Overall base width: 0.48 m
Overall length: 1.17 m
Pitch rung/tread: 216 mm
Standards: EN 131 professional
Stile depth: 40 mm
Transport dimensions: 1.170 mm × 480 mm × 160 mm
Tread depth: 80 mm
Type rung/tread: serrated
Vertical ladder height: 1.09 m
Warranty: 10 years
Weight: 4.8 kg
Working height: 2.65 m

## Hints and special features

Complies with EN 131 Professional.

## Accessories and spare parts

| Image | Order number | Name | Type |
|---|---|---|---|
| | 40920 | Hook-on tool box | Accessory |
| | 40251 | Horizontal stabiliser bar for retrofitting | Parts list |
| | 800266 | Push-on end cap | Spare part |