

Coni B

Whenever you need access to great heights: flexibility with up to 20 rungs for working heights of up to 6.70 m.

Product description

- Sturdy aluminium alloy rungs (30 x 30 mm) with non-slip serrated surface.
- Sturdy, solidly screwed steel hinges
- Two high-strength Perlon belts, secured without twisting to the rung, prevent splay.
- High strength, non-twist rung/stile connections.
- Additional stabilisation by bracing on the bottom rung.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.



Product features

Anti splay: Belt strap
 Coating: natural
 Connection Stile-Rung: flanged
 Load: max. 150 kg
 Material: Aluminium
 Pitch rung/tread: 265 mm
 Producttype: Flanged stepladder with rungs
 Tread depth: 30 mm
 Type rung/tread: serrated

Hints and special features

Stepladder for maximum working heights of up to 6.70 m.
 Complies with EN 131 Professional.

Product variants

Order number	Base	Number of rungs	Number of rungs	Overall base width	Overall length	Stile depth	Transport dimensions	Vertical ladder height	Weight	Working height
40274	0,9 m × 0,47 m	4	2 × 4	0,47 m	1,22 m	50 mm	1.220 mm × 470 mm × 140 mm	1,2 m	4,4 kg	2,5 m
40275	1,07 m × 0,5 m	5	2 × 5	0,5 m	1,58 m	58 mm	1.500 mm × 505 mm × 140 mm	1,46 m	5,8 kg	2,75 m
40311	1,25 m × 0,53 m	6	2 × 6	0,53 m	1,78 m	58 mm	1.810 mm × 533 mm × 155 mm	1,73 m	6,8 kg	3 m
40277	1,41 m × 0,57 m	7	2 × 7	0,57 m	2,06 m	58 mm	2.080 mm × 570 mm × 155 mm	1,99 m	7,3 kg	3,25 m
40312	1,36 m × 0,59 m	8	2 × 8	0,59 m	2,34 m	58 mm	2.363 mm × 593 mm × 155 mm	2,3 m	9 kg	3,55 m
40313	1,65 m × 0,65 m	10	2 × 10	0,65 m	2,9 m	58 mm	2.922 mm × 653 mm × 155 mm	2,83 m	11,1 kg	4,05 m
40314	1,94 m × 0,71 m	12	2 × 12	0,71 m	3,46 m	58 mm	3.481 mm × 713 mm × 155 mm	3,37 m	13,3 kg	4,6 m
40315	2,23 m × 0,77 m	14	2 × 14	0,77 m	4,02 m	62 mm	4.041 mm × 773 mm × 163 mm	3,91 m	17,2 kg	5,1 m



Order number	Base	Number of rungs	Number of rungs	Overall base width	Overall length	Stile depth	Transport dimensions	Vertical ladder height	Weight	Working height
40316	2,52 m × 0,83 m	16	2 × 16	0.83 m	4.58 m	68 mm	4.600 mm × 833 mm × 183 mm	4.45 m	21.2 kg	5.65 m
40320	2,83 m × 0,89 m	18	2 × 18	0.89 m	5.14 m	73 mm	5.160 mm × 893 mm × 185 mm	5 m	25.6 kg	6.15 m
40317	3,12 m × 0,95 m	20	2 × 20	0.95 m	5.7 m	73 mm	5.720 mm × 953 mm × 185 mm	5.54 m	29.8 kg	6.7 m