
EFA B

For flexible applications in electrical or chemical environments and for working under voltage.



Product description

- For flexible applications in electrical or chemical environments and for working under voltage.
- Stiles and rungs made of glass-fibre-reinforced plastic for particularly high chemical resistance.
- Complies with the high-voltage test for ladders of insulating material in accordance with DIN EN 61 478 or VDE 0682 Section 6.5 Category 1/30 KV.
- Resistance to ageing in accordance with DIN EN ISO 4892-2.
- Suitable for working in high-voltage environments (1000 V AC, 1500 V DC).
- Stiles and rungs (30 x 30 mm) made from glass-fibre-reinforced plastic for particularly high chemical resistance.
- High-strength perlon belts prevent splay.
- Replaceable 2-component plastic end caps ensure positioning without the risk of slipping and at the same time provide firm seating in the stile.



Hints and special features

Complies with EN 131 Professional.

Product features

Anti splay: Belt strap
Load capacity: max. 150 kg
Material: Glass-fibre reinforced plastic
Pitch rung/tread: 265 mm
Standards: EN 131 professional
Stile depth: 58 mm
Tread depth: 30 mm
Type rung/tread: serrated
Warranty: 10 years

Product variants

Order number	Base	Number of rungs	Number of rungs	Overall base width	Overall length	Transport dimensions	Vertical ladder height
41261	1,08 m × 0,48 m	4	2 × 4	0.48 m	1.32 m	1.350 mm × 480 mm × 162 mm	1.27 m
41256	1,31 m × 0,54 m	6	2 × 6	0.54 m	1.88 m	1.900 mm × 540 mm × 162 mm	1.82 m
41257	1,66 m × 0,6 m	8	2 × 8	0.6 m	2.44 m	2.460 mm × 600 mm × 162 mm	2.35 m
41258	2,01 m × 0,66 m	10	2 × 10	0.65 m	3 m	3.000 mm × 660 mm × 160 mm	2.89 m
41260	2,7 m × 0,78 m	14	2 × 14	0.77 m	4.12 m	4.150 mm × 770 mm × 160 mm	3.95 m

Order number	Weight	Working height

Order number	Weight	Working height
41261	7.5 kg	2.6 m
41256	10.5 kg	3.1 m
41257	13.8 kg	3.65 m
41258	17 kg	4.15 m
41260	24.6 kg	5.2 m