

ZAP Safemaster S

Safe ascent and descent due to non-slip treads and handrail, high degree of stability and compact transport dimensions.

Product description

- · Safe ascent and descent due to non-slip treads and handrail, high degree of stability and compact transport dimensions.
- Optimum stability thanks to rigid locking bar on both
- Foldable anodised handrails allow it to take up less space during transport.
- The handle on the platform allows the ladder to be folded up quickly and effortlessly.
- Extra-large work platform (400 x 400 mm).
- Anodised handrails and guardrails.
- Generously sized storage tray for tools and small
- Treads 80 mm deep, with ZARGES Safer Step Technology.
- Can be retrofitted with optional stabiliser sets to comply with EN 131, Part 7.



Anti splay: Rigid locking bar Guardrail height: 1000 mm Load capacity: max. 150 kg Platform length: 400 mm

Platform material: Aluminium ribbed plate

Platform width: 400 mm Standards: EN 131 professional

Stile depth: 73 mm Stile depth: 58 mm

Stile depth steps/back stay: 73mm / 58mm

Tray: Aluminium Tread depth: 80 mm Type rung/tread: Safer Step

Warranty: 10 years





Product variants

Order number	Height including railing	Number of rungs, incl. platform	Overall base width	Overall length	Platform height	Transport dimensions	Weigh t
41672	1.53 m	2	0.59 m	1.87 m	0.53 m	approx. 1.870 mm × 620 mm × 210 mm	10.6 kg
41681	1.79 m	3	0.62 m	2.15 m	0.79 m	approx. 2.150 mm × 620 mm × 210 mm	11.8 kg
41674	2.06 m	4	0.65 m	2.43 m	1.06 m	approx. 2.430 mm × 630 mm × 210 mm	13 kg

ZARGES GmbH Zargesstraße 7 Tel: +49 (0)881-687-0 Fax: +49 (0)881-687-0 www.zarges.com internationalsales@zarges.de



Order number	Height including railing	Number of rungs, incl. platform	Overall base width	Overall length	Platform height	Transport dimensions	Weigh t
41675	2.32 m	5	0.68 m	2.71 m	1.32 m	approx. 2.710 mm × 680 mm × 210 mm	14.4 kg
41676	2.6 m	6	0.71 m	2.99 m	1.58 m	approx. 2.990 mm × 700 mm × 210 mm	16.1 kg
41677	2.87 m	7	0.74 m	3.27 m	1.85 m	approx. 3.270 mm × 720 mm × 210 mm	17.4 kg
41678	3.13 m	8	0.77 m	3.55 m	2.11 m	approx. 3.550 mm × 750 mm × 210 mm	19.1 kg
41679	3.4 m	9	0.8 m	3.83 m	2.34 m	approx. 3.830 mm × 773 mm × 210 mm	20.4 kg

Order number	Working height
41672	2.53 m
41681	2.79 m
41674	3.06 m
41675	3.32 m
41676	3.58 m
41677	3.85 m
41678	4.11 m
41679	4.34 m