

ZAP Telemaster S

Safe and flexible: height-adjustable platform with peripheral railing for safe standing, easy to move and folds to compact dimensions.

Product description

- Height-adjustable platform with large standing surface and all-round railings for safe and comfortable footing.
- Simple height adjustment according to the push-up ladder principle, allowing different heights to be reached with only one platform ladder.
- Very easy to erect - handrails and guard rails are automatically unfolded during erection.
- Can be used on stairs and folded to a very compact size for transport and storage.
- The two rear wheels make it easy to move.
- Large standing surface, 665 × 440 mm, made of 7-ply adhesive-bonded plywood board, with guardrail and knee bar, ensures maximum work safety and comfortable standing.
- Complies with new European standard DIN EN 131-7.
- Can be easily pushed thanks to two wheel assemblies, even when erected.
- Compact dimensions when folded, therefore easy to transport and store.
- High strength, non-twist rung/stile connections.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.
- Can be used on steps / stairs.
- Order No. 41325 without stabiliser.
- Number of ballast weights required when used in an outdoor area: 4x (Order No. 41331).



Product features

Guardrail height: 1 m
 Length: 0.4 m
 Load capacity: max. 150 kg
 Platform length: 665 mm
 Platform material: 7-layer laminated plywood
 Platform width: 440 mm
 Standards: EN 131-7
 Tray: Aluminium
 Tread depth: 30 mm
 Warranty: 10 years

Product variants



| Order number | Footpoint, stabiliser rod extended L x W | Footpoint, stabiliser rod retracted L x W | Height including railing | No. of rungs incl. platform | Platform height | Transport dimensions | Weight |
|--------------|--|---|--------------------------|-----------------------------|--|------------------------------|---------|
| 41325 | 1,45m x 1 m | 1,45m x 1 m | max. 2.37 m | 5 | 0,81m / 1,08m / 1,34m | 2.160 mm x 1.020 mm x 400 mm | 28 kg |
| 41326 | 1,8m x 2,25 m | 1,8m x 0,81 m | max. 2.86 m | 7 | 1,05m / 1,3m / 1,6m / 1,83m | 2.440 mm x 820 mm x 400 mm | 34 kg |
| 41327 | 2,2m x 2,55 m | 2,2m x 0,81 m | max. 3.38 m | 9 | 1,31m / 1,6m / 1,8m / 2,1m / 2,35m | 2.720 mm x 820 mm x 400 mm | 38.5 kg |
| 41328 | 2,8m x 2,5 m | 2,8m x 0,81 m | max. 4.17 m | 12 | 1,83m / 2,12m / 2,38m / 2,65m / 2,9m / 3,15m | 3.280 mm x 820 mm x 400 mm | 50 kg |

| Order number | Width | Width extended | Width retracted | Working height | closed length | extended length |
|--------------|--------|----------------|-----------------|----------------|---------------|-----------------|
| 41325 | 2.16 m | 1 m | 1 m | 3.34 m | 1.45 m | 1.45 m |
| 41326 | 2.44 m | 2.25 m | 0.81 m | 3.83 m | 1.8 m | 1.8 m |
| 41327 | 2.72 m | 2.55 m | 0.81 m | 4.35 m | 2.2 m | 2.2 m |
| 41328 | 3.28 m | 2.5 m | 0.81 m | 5.15 m | 2.8 m | 2.8 m |