

# MultiTower S-PLUS 1T, 1,80 m

The mobile scaffolding solution for quick and safe erection due to advanced guardrails, two-metre platform spacing and fewer individual parts.

## Product description

- Scaffold width: 0.75 m; scaffold length: 1.80 m.
- Safe and quick assembly and dismantling due to advanced guardrail (instead of railings and diagonal braces) and platforms at intervals of 2 m.
- Working heights can be extended from 3.35 m to max. 13.20 m with standard parts.
- Scaffolding category 3 (can be loaded up to 200 kg/m<sup>2</sup>) according to DIN EN 1004, i.e. depending on platform length from 202 kg to max. 286 kg.
- Standard castors: height-adjustable 200 mm swivel castors (Order No. 42917) for millimetre-perfect level adjustment.



## Hints and special features

Standard Z 600 mobile scaffold towers with stabilisers can also be retrofitted for stable set-up by adding the relevant S-PLUS single parts.

## Product features

Length as work platform: 1.8 m  
 Platform size: 0,6m × 1,8m  
 Platform width: 0.6 m

## Product variants

Order number	Overall height	Platform height	Transport dimensions	Weight	Working height
52225	2.65 m	1.4 m	2.100 mm × 900 mm × 400 mm	75.2 kg	3.4 m
52235	3.75 m	2.5 m	2.100 mm × 900 mm × 500 mm	117.8 kg	4.5 m
52245	4.6 m	3.35 m	2.100 mm × 900 mm × 600 mm	145.4 kg	5.35 m
52255	5.7 m	4.45 m	2.100 mm × 900 mm × 700 mm	158.6 kg	6.45 m
52265	6.55 m	5.3 m	2.100 mm × 900 mm × 800 mm	186.2 kg	7.3 m
52275	7.65 m	6.4 m	2.100 mm × 900 mm × 900 mm	199.4 kg	8.4 m
52285	8.5 m	7.25 m	2.100 mm × 900 mm × 1.000 mm	234.6 kg	9.25 m
52295	9.65 m	8.4 m	2.100 mm × 900 mm × 1.100 mm	247.8 kg	10.4 m
52305	10.45 m	9.2 m	2.100 mm × 900 mm × 1.200 mm	275.4 kg	11.2 m
52315	11.6 m	10.35 m	2.100 mm × 900 mm × 1.400 mm	288.6 kg	12.35 m



Order number	Overall height	Platform height	Transport dimensions	Weight	Working height
52325	12.45 m	11.2 m	2.100 mm × 900 mm × 1.500 mm	316.2 kg	13.2 m