

# MultiTower S-PLUS 1T, 2,50 m

The mobile scaffolding solution for quick and safe erection due to advanced guardrails, two-metre platform spacing and fewer individual parts.

## Product description

- Scaffolding width: 0.75 m; scaffolding length: 2.50 m.
- Safe and quick assembly and dismantling due to advanced guardrail (instead of railings and diagonal braces) and platforms at intervals of 2 m.
- Working heights can be extended from 3.35 m to max. 13.20 m with standard parts.
- Scaffolding category 3 (maximum load of 200 kg/m<sup>2</sup>) according to DIN EN 1004.
- Standard castors: height-adjustable 200 mm swivel castors (Order No. 42917) for millimetre-perfect level adjustment.



## Product features

Length as work platform: 2.5 m  
 Platform size: 0,6m × 2,5m  
 Platform width: 0.6 m

## Product variants

Order number	Overall height	Platform height	Transport dimensions	Weight	Working height
52226	2.65 m	1.4 m	2.800 mm × 900 mm × 400 mm	85.9 kg	3.4 m
52236	3.75 m	2.5 m	2.800 mm × 900 mm × 500 mm	132.5 kg	4.5 m
52246	4.6 m	3.35 m	2.800 mm × 900 mm × 600 mm	168.8 kg	5.35 m
52256	5.7 m	4.45 m	2.800 mm × 900 mm × 700 mm	182.8 kg	6.45 m
52266	6.55 m	5.3 m	2.800 mm × 900 mm × 800 mm	219.1 kg	7.3 m
52276	7.65 m	6.4 m	2.800 mm × 900 mm × 900 mm	233.1 kg	8.4 m
52286	8.5 m	7.25 m	2.800 mm × 900 mm × 1.000 mm	277.8 kg	9.25 m
52296	9.65 m	8.4 m	2.800 mm × 900 mm × 1.100 mm	291.8 kg	10.4 m
52306	10.45 m	9.2 m	2.800 mm × 900 mm × 1.200 mm	328.1 kg	11.2 m
52316	11.6 m	10.35 m	2.800 mm × 900 mm × 1.300 mm	342.1 kg	12.35 m

## Hints and special features

Standard Z 600 mobile scaffold towers with stabilisers can also be retrofitted for stable set-up by adding the relevant S-PLUS single parts.



Order number	Overall height	Platform height	Transport dimensions	Weight	Working height
52326	12.45 m	11.2 m	2.800 mm × 900 mm × 1.400 mm	378.4 kg	13.2 m