

MultiTower S-PLUS 2T, 1,80 m - 52455

Maximum working area, safe and quick erection through advanced guardrail, low platform spacing and fewer single parts.

Product description

- Maximum working area, safe and quick erection through advanced guardrail, low platform spacing and fewer single parts.
- Safe and quick assembly and dismantling due to advanced guardrail (instead of railings and diagonal braces) and platforms at intervals of 2 m.
- Scaffolding width: 1.35 m; scaffolding length: 1.80 m.
- Working heights can be extended from 3.35 m to max. 13.20 m with standard parts.
- Scaffolding category 3 (maximum load of 200 kg/m²) according to DIN EN 1004.
- Standard castors: height-adjustable 200 mm swivel castors (Order No. 42917) for millimetre-perfect level adjustment.



Product features

Claw type: automatic
 Height-adjustable castors: Yes
 Overall height: 5.7 m
 Platform height: 4.45 m
 Platform length: 1.8 m
 Platform width: 1.2 m
 Platform size: 1,2m × 1,8m
 Rung diameter: 50 mm
 Scaffolding class: 3 (= 200 kg/m²)
 Standards: EN 1004-1
 Stile diameter: 50 mm
 Transport dimensions: 2.100 mm × 1.500 mm × 700 mm
 Warranty: 10 years
 Weight: 197.1 kg
 Wheel diameter: 200 mm
 Width scaffolding: 1.35 m
 Working height: 6.45 m

Hints and special features

Standard Z 600 mobile scaffold towers with stabilisers can also be retrofitted for stable set-up by adding the relevant S-PLUS single parts.

Accessories and spare parts

Image	Order number	Name	Type
	800172	Spring clip for scaffolding	Spare part