

# Single-section fixed ladder systems, access height of up to 10 m, anodised aluminium

Stationary access to buildings and machinery up to a height of 10 m, also suitable and approved for use as an escape route.

## Product description

- For stationary mounting, on buildings either for maintenance in accordance with DIN 18 799-1 or as an emergency ladder system in accordance with DIN 14 094-1 or as machine access steps in accordance with DIN EN ISO 14 122-4.
- Back cage as safety system, complies with any standard.
- Arrestor rail as a safety system in accordance with DIN EN 353-1, DIN 18 799-1 and DIN EN ISO 14 122-4, can be supplied as a single-section fixed ladder even with climbing heights of over 10 m.
- Ladder width: 520 mm.
- Wall brackets with various wall distances up to 600 mm can be selected.
- The distance between the wall brackets is max. 2.00 m. But each ladder section must be mounted with at least 2 wall brackets.
- Safety barriers, access protection and platforms can be selected to suit individual requirements.
- On request, we can also produce fixed-ladders that differ from the standard specifications.

## Product features

Material: Anodised aluminium

## Product variants

Order number	Overall length incl. stile	access height
58148	5.9 m	4.8 m
58157	6.7 m	5.6 m
58165	7.6 m	6.5 m
58174	8.5 m	7.4 m
58185	9.6 m	8.5 m



## Hints and special features

Dowels and screws/bolts for wall mounting are not included in the scope of delivery. The prices for single-section systems listed below are calculated as follows: Wall bracket in the form of a U-bar, 200 mm rigid, straight stile extensions on both sides, incl. back cage in accordance with DIN 18 799-1. In the case of other requirements, please use our planning system for fixed ladders.



Order number	Overall length incl. stile	access height
58196	10.7 m	9.6 m