

Multi-section fixed ladder systems, anodised aluminium

Multi-section access solution with crossover platform for buildings and machinery.

Product description

- For permanent installation to BGV D 36 and DIN 18 799-1, DIN 14 094-1 and EN ISO 14 122-4.
- With back guards.
- Ladder width: 520 mm.
- Wall brackets with various wall distances up to 600 mm can be selected.
- The distance between the wall brackets is max. 2.00 m. But each ladder section must be mounted with at least 2 wall brackets.
- Safety barriers, access protection and platforms can be selected to suit individual requirements.
- On request, we can also produce fixed-ladders that differ from the standard specifications.

Product features

Material: Anodised aluminium

Product variants

Order number	Overall length incl. stile	access height
58507	11.8 m	10.7 m
58518	12.9 m	11.8 m
58526	13.7 m	12.6 m
58538	14.9 m	13.8 m
58549	16 m	14.9 m
58557	16.8 m	15.7 m
58568	17.9 m	16.8 m
58580	19.1 m	18 m
58591	20.2 m	19.1 m



Hints and special features

Dowels and screws/bolts for wall mounting are not included in the scope of delivery. The prices for double-section systems listed below are calculated as follows: Wall bracket in the form of a U-bar, 200 mm rigid, straight stile extensions on both sides, crossover platform, incl. back cage in accordance with DIN 18 799-1. In the case of other requirements, please use our planning system for fixed ladders.