

Aluminium shaft covers with cover trough

Shaft covers that can be walked or driven on, with customisable inner and outer surface.

Product description

- Compliant with DIN EN 124 in conjunction with DIN 1229.
- Tapering section design, therefore easy to open. No sticking.
- Easy to open, no jamming.
- EPDM seal (petrol-resistant seal available on request).
- Odour-tight and impervious to surface water.
- Load with choice of surface: test force 125 kN (=12.5 t), only after cover trough has been filled by customer with B 45 concrete (grain 0-8).
- Incl. lift-out handles (pair) made from stainless steel, comprising one self-lifting opening handle and one lift-out handle.



Product features

Design height: 80 mm
 Material, cover: Aluminium
 Material, frame: Aluminium
 Trough depth: 60 mm

Product variants

Order number	Inside shaft length	Inside shaft size	Inside shaft width	Outside dimensions L x W x H	Transport dimensions
47000	300 mm	300mm x 300mm	300 mm	440 mm x 440 mm	440 mm x 440 mm x 70 mm
47001	450 mm	450mm x 450mm	450 mm	590 mm x 590 mm	590 mm x 590 mm x 70 mm
47002	500 mm	500mm x 500mm	500 mm	640 mm x 640 mm	640 mm x 640 mm x 70 mm
47004	600 mm	600mm x 600mm	600 mm	740 mm x 740 mm	740 mm x 740 mm x 70 mm
47005	635 mm	635mm x 635mm	635 mm	775 mm x 775 mm	770 mm x 770 mm x 70 mm
47007	800 mm	800mm x 800mm	800 mm	940 mm x 940 mm	940 mm x 940 mm x 70 mm
47010	1000 mm	1.000mm x 1.000mm	1000 mm	1.140 mm x 1.140 mm	1.140 mm x 1.140 mm



Order number	Inside shaft length	Inside shaft size	Inside shaft width	Outside dimensions L x W x H	Transport dimensions
		1.000mm			× 70 mm