

W 170 trolley

The all-rounder: a sturdy box trolley for universal applications, for in-company logistics or for the transportation of waste.

Product description

- Robust and durable due to many quality features, e.g. sturdy, generously dimensioned edge and base profile, permanent connection to jacket and base plate using high-strength positive locking, riveted shell joint and welded frame profiles.
- High stiffness due to end and side walls reinforced with peripheral beading and corner beads.
- Effortless to manoeuvre due to easy-running, nonmarking rubber wheels that are mounted on roller bearings and equipped with thread guards.
- Sturdy, generously dimensioned edge and base profile sections, high-strength positive locking ensures permanent bonding to jacket and base metal.
- End and side walls reinforced with peripheral beading and corner beads.
- Running gear: 2 swivel and 2 fixed castors, corner-mounted, Ø 125 mm, 40 mm wide, easy running, rubber wheels, "non-marking", roller bearings, thread guards.
- Casing joint riveted throughout. Frame profile sections welded.



Chassis arrangement can be changed: Yes

Corner beading: Yes

Formation Chassis: 2 swivel and 2 fixed castors

mounted at the corners Material: Aluminium Peripheral beading: Yes Wheel diameter: 125 mm Wheel diameter: 40 mm



Order number	Internal dimensions L x W x H	Outside dimensions L x W x H	Volume	Weight
40631	1.000 mm × 640 mm × 650 mm	1.050 mm × 690 mm × 855 mm	415 l	19.5 kg
40635	1.250 mm × 700 mm × 750 mm	1.300 mm × 750 mm × 955 mm	655 l	23.7 kg

