

W 161 Spring Loaded Trolleys

No more bending: easy access to the contents of the trolley for ergonomic working, for example in libraries, laundries or in the catering trade.

Product description

- The base can move vertically to keep the contents at a constant height for easy access and work ergonomics.
- Depending on the type of trolley, the load capability can be varied from 30 to 195 kg in increments of 15 kg by means of replaceable lifting elements.
- The moveable base does not tilt, even when loaded on only one side.
- Sturdy, generously dimensioned edge and base profile sections, high-strength positive locking ensures permanent bonding to side walls and base.
- Beading for increased stability.
- Effortless to manoeuvre due to easy-running, nonmarking rubber wheels that are mounted on roller bearings and equipped with thread guards.
- Trolley with vertically moveable base which keeps the load at constant height for easy access.
- Anodised, edge profile reinforced with abrasionresistant plastic padding.
- Running gear: 2 swivel and 2 fixed castors, Ø 125 mm, 40 mm wide, easy running, rubber wheels, "nonmarking", roller bearings, thread guards.
- Castors arranged centrally for easy manoeuvring, even in the most confined spaces.
- Corner-mounted running gear available on request.

Product features

Chassis arrangement can be changed: Yes Corner beading: Yes Formation Chassis: 2 swivel and 2 fixed castors in center arrangement Material: Anodised aluminium Wheel diameter: 125 mm Wheel diameter: 40 mm

Product variants

Order number	Internal dimensions L x W x H	Outside dimensions L x W x H	Spring force	Volume	Weight	
40644	1.000 mm × 650 mm × 485 mm	1.060 mm × 710 mm × 820 mm	90 kg	315 l	24.5 kg	
40756	1.410 mm × 700 mm × 580 mm	1.460 mm × 750 mm × 920 mm	150 kg	570 l	31.5 kg	
ZARGES GmbH		Tel: +49 (0)881-687-0		www.zarges.com		
Zargesstraße 7		Fax: +49 (0)881-687-0		international- sales@zarges.de		Effective 4/20/2024
D-82362 Weilheim		Errors and omissions excepted.				1/1



