

K 470 universal case, IP 65

For all applications where extra leak-tightness and greater protection against moisture, water jets and dust is required.

Product description

- For all applications where extra leak-tightness and greater protection against moisture, water jets and dust is required.
- Protection class IP 65 in accordance with EN 60 529 through foamed seal in the lid.
- 3 standard sizes ex stock, customised versions available on request.
- Also available with approval for the transportation of hazardous goods.
- Extra thick 1.5-mm sheet metal for all K 470 containers from basic dimensions of 750 x 550 mm.
- Automatic pressure compensation membrane
- Leak-tightness verified with TÜV SÜD certificate.
- Available for most K 470 models.
- 3 standard sizes available from stock.



Product features

Colour of the stacking corners: Natural aluminium
 Corner beading: Yes
 Fasteners: Comfort fasteners
 Integrated wheels: No
 Material: Aluminium
 Material of the stacking corners: Aluminium
 Number of handles: 2
 Peripheral beading: Yes
 Protection class: IP65:
 Seal: foamed lid seal
 Stacking corners: Yes
 Warranty: 10 years

Hints and special features

UN approval for the transportation of hazardous goods possible at additional charge.
 Clearance measurement approx. 30mm (1.2") less than internal dimension (length and width). Special sizes on request.

Product variants

Order number	Internal dimensions L x W x H	Max. gross weight dangerous goods permission	Outside dimensions L x W x H	Volume	Weight
366206	550 mm x 350 mm x 380 mm	75 kg	600 mm x 400 mm x 410 mm	73 l	5.3 kg
366217	750 mm x 550 mm x 380 mm	102 kg	800 mm x 600 mm x 410 mm	157 l	10 kg
366218	750 mm x 550 mm x 580 mm	126 kg	800 mm x 600 mm x 610 mm	239 l	12 kg